



## Features

- LED retrofit replacement for halogen low voltage capsules Compact design Omni-directional light distribution 12V AC/DC 300lm = 28W halogen G4 lamp High lumen efficacy: 125lm/W 91% energy saving A++ energy rating Non-dimmable Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications

## Product Overview

Product name	ToLEDo G4 300lm 827 SL
Technology	LED
Watt (Rated) (W)	2.4
Cap/Base	G4
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740761
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	2.4
Power consumption (W)	2.4
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288282442
Warranty	3 years
Useful luminous flux (#use)	300

## Data table

### GENERAL DATA

Product name	ToLEDo G4 300lm 827 SL
Technology	LED
Watt (Rated) (W)	2.4
Cap/Base	G4
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740761
Warranty	3 years

### OPTICAL DATA

Useful luminous flux (#use)	300
Luminous flux (Rated) (lm)	300
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300

### ELECTRICAL DATA

Power consumption (W)	2.4
Wattage (W)	2.4
Starting time (max) (s)	#0.5
Warm-up time to 60% of full light (max) (s)	#1
Primary Supply/Product voltage - min (V)	12
Primary Supply/Product voltage - max (V)	12
Lamp power factor	0.5

## ToLEDo G4 300lm 827 SL 0028244

Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Nominal Frequency (Hz)	50/60/HF

### LIFETIME DATA

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### PHYSICAL DATA

Nominal Product Length (mm)	44
Nominal Product Diameter (mm)	13
Weight (kg)	0.045

### PACKAGING

Product EAN number	5410288282442
Packaging single length / height (cm)	6.7
Packaging single width (cm)	2.8
Packaging single depth (cm)	2.8
DUN14 (inner)	15410288282449
Units per inner package	10
Packaging inner length / height (cm)	7.7
Packaging inner width (cm)	6.5
Packaging inner depth (cm)	15.5
DUN14 (outer)	25410288282446
Units per outer package	100
Packaging outer length / height (cm)	18.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	17.0

### SAFETY DATA

Breakage cleaning instructions	Not applicable
--------------------------------	----------------

ToLEDo G4 300lm 827 SL  
**0028244**

<b>Special purpose lamp</b>	No
<b>Dry applications use only</b>	Yes
<b>Suitable for household illumination</b>	Yes
<b>Safety message</b>	Suitable for approved transf./dimmers
<b>Safety message</b>	Not Suitable for totally enclosed fixtures