

Sylveo LED - Extra Large

SYLVEO LED 20000LM ROAD ASYMMETRIC 4K DALI
0049147



Product features

- Exterior LED floodlight, comes complete with a 1000mm cable and adjustable bracket, aluminium housing, clear glass diffuser, 21542lm, 201W, 107lm/W, 4000K, 5002mA, CRI70, 52°x117° beam angle, DALI dimmable, IP66, IK08, Class I, 50000hrs, (LxWxD) 98x496x392mm




PRODUCT OVERVIEW

| | |
|-----------------------------------|--|
| Product name | SYLVEO LED 20000LM ROAD ASYMMETRIC 4K DALI |
| Technology | LED |
| Housing | Aluminium |
| Mount | Wall surface mounted |
| Fixture rating | Enclosed |
| General application | Logistics & Industry |
| ETIM Class | EC001744 |
| E-number FI | 4579405 |
| E-number SE | 7764813 |
| Warranty | 5 years |
| Useful luminous flux (Fuse) | 21542 |
| Fixture luminous flux (lm) | 21542 |
| Luminaire efficacy (lm/W) | 107 |
| LOR (%) | 100 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 70 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 52 x 117 |
| Glare control | < 18 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 202 |
| Electrical protection | Class I |
| Control gear type | Electronic ballast |
| Dimmable | Yes |
| Dimming method | DALI |
| Minimum dimming level (%) | 1 |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | RAL 9006 - Aluminium |
| IP rating | IP66 |
| IK rating | IK08 |
| Product EAN number | 5410288491479 |

Sylveo LED - Extra Large SYLVEO LED 20000LM ROAD ASYMMETRIC 4K DALI 0049147

PHOTOMETRY



TECHNICAL DRAWINGS

