

## Twofold faceplate, vertical 71 mm centre distance, for a double switch and one 45x45 function, Niko Rocker alu black brushed


**224-56856**



The Niko Rocker twofold vertically oriented faceplate clicks onto a single switch function and one 45 x 45 mm function that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker double switch function and a Niko 45 x 45 mm function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu black for Niko Rocker and Niko Toggle finishing sets and black coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function



### Technical data

Twofold faceplate, vertical 71 mm centre distance, for a double switch and one 45x45 function, Niko Rocker alu black brushed.

- Double faceplate for two switches.
- Colour faceplate: alu black brushed
- Colour RAL (approximately): 000 20 00
- Colour NCS (approximately): NCS S 8005-R50B
- Recommended colour central plate: alu black for Niko Rocker and Niko Toggle finishing sets and black coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled black
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.

- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 154 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 154 mm
- Marking: EU