

Product data sheet Spirotech

Product name

SpiroVent Superior S600 -Refill

Article number

MV06R50

Product properties

A fully automatic vacuum degasser for closed heating, cooling and process systems with a pressure between 2.5 and 6 bar.

I: insulated


B: with break tank

R: with direct refill

Product image



Product dimensions



Product data sheet Spirotech

ETIM product data

Height	1020 mm
With insulation	No
Max. glycol mixture	40 %
Article compression class	PN 10
Suitable for closed system	Yes
With integrated replenishment automat	Yes
Max. installation contents	325000 l
Width	673 mm
Depth	360 mm
Max. flow rate	1000 l/h
Connection size inlet	3/4 inch
Connection inlet	External thread cylindrical BSPP-G (ISO 228-1)
Connection size outlet	3/4 inch
Connection outlet	External thread cylindrical BSPP-G (ISO 228-1)
Connection size refill/top-up	3/4 inch
Connection type refill/top-up	Internal thread cylindrical BSPP-G (ISO 228-1)

Frequency	50 Hz
Sound pressure level	57 dB(A)
Degree of protection (IP)	IP44
With backflow safeguard	No
LAN connection	Yes
Max. electric power input	0.8 kW
Wi-Fi	Yes
With communication interface RS-485	Yes
Communication interface inverter MOD-Bus	Yes
Bluetooth	No
Supporting protocol for BACnet	No
Potential free switch contact	Yes
Touchscreen operation	Yes
Remote controllable function	Yes
Nominal current	5.1 A

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website

