

Product certificate K46015/02

Issued 2015-12-01

Replaces K46015/01

Page 1 of 2

Frost resistant outdoor taps with wall passage

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by


Seppelfricke Armaturen GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K14001/04: "Sanitary tapware: Frost resistant outdoor taps with wall passage", dated 01-02-2012,

which covers the requirements of

EN 200: 2008: "Sanitary tapware: General technical specifications for single taps and mixer taps (nominal size ½) PN 10: Minimum flow pressure of 0.05 Mpa (0.5 Bar)".



Bouke Meekma
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl



289/150609

Supplier

Seppelfricke Armaturen GmbH
Haldenstrasse 27RK1
45881 GELSENKIRCHEN
Germany
Tel. +49.2094040
Fax +49.209404496
www.seppelfricke.com

**Certification process
consists of initial and
regular assessment of:**

- quality system
- product

Frost resistant outdoor taps with wall passage

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate:

SEPP-Eis frost free outer wall valve set

Model, size, description:

Model 8041, DN15, with T-handle;

Model 8044, DN15, same as model 8041 but with head piece for box spanner.

REMARK

The above listed products were not yet assessed for compliance with all hygienic aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 19 July 2011, as specified in clause 4.2.1 of the Kiwa Evaluation guideline BRL-K14001/04.

APPLICATION AND USE

The sanitary tapware: frost resistant outdoor taps with wall passage are intended for application in drinking water installations with a static water pressure of maximum 1000 kPa and a maximum water temperature of 90 °C.

The recommended limits for correct operation are a dynamic pressure between 100 kPa and 500 kPa and a water temperature of maximum 65°C.

MARKING

The products are marked with the word mark "KIWA" and the abbreviated mark "KK" in a rectangle.

Place of the mark:

- on the body: "KIWA";
- on the head part: "KK" in a rectangle.

Compulsory specifications:

- manufacturer's identification mark: on the body and the head part:

Method of marking:

- non-erasable;
- visible after installation.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Seppelfricke Armaturen GmbH
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.