

Product data sheet

Item No. 96.453.4034.1

Cable assembly RST20I5KS-S 25 40SW

Connection cable, male - free end, length 4m, RST20i5, 5 pole, 250/400V, 20A, cable type H07RN-F, cross section 2,5 mm², color of coding: black



Item No.	96.453.4034.1
EAN	4015573919952
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	13.5 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Kabeltype/cable type H07RN-F5G2,5

Kodierung/Keying 0
(250V/20A)

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.453.XX34.1	XX in dm-Schritten	96.453.1034.1 = 100dm = 1000m	RST201SKS-S 25 106L
96.453.XX34.0		96.453.1034.0	RST201SKS-S 25 106L
06.453.XX34.1	XX in m-Schritten	06.453.1234.1 = 12 m/L=12000m	RST201SKS-S 25 X120M
06.453.XX34.0		06.453.1234.0	RST201SKS-S 25 X120M

96.453.1034.0	01K
---------------	-----

KONFEKT_LEITUNG

Sitzabstimmung: Bitte beachten Sie die Anschlussbedingungen in der Bedienungsanleitung.