



START SURFACE IP66 1250LM 840 IK10 WHT

Item No: 0049929




Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.42 1.39	1880 199
1.0	2.85 2.78	471 49
1.5	4.27 4.17	188 18
2.0	5.69 5.57	104 10
2.5	7.11 6.96	67 7
3.0	8.54 8.35	46 4



START SURFACE IP66 1250LM 840 IK10 WHT

Item No: 0049929



General data

Product name	START SURFACE IP66 1250LM 840 IK10 WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor, Outdoor
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4579600
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	1250
Fixture luminous flux (lm)	1250
Luminaire efficacy (lm/W)	105
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Distribution type	Diffuse, Symmetric
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	12
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.83
Electrical protection	Class II
Control gear type	LED driver constant current
Dimming method	N/A
Inrush Current (A)	20
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	38
Max. products per 13A C Breaker	47
Max. products per 16A C Breaker	57
Max. products per 20A C Breaker	66
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B50	78000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	90
Nominal Product Diameter (mm)	300
Weight (kg)	0.78

START SURFACE IP66 1250LM 840 IK10 WHT

Item No: 0049929



Packaging

Product EAN number	5410288499291
Packaging single width (cm)	9.9
Packaging single depth (cm)	30.5
DUN14 (inner)	15410288499298
Packaging outer length / height (cm)	61.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40