



START SURFACE IP66 1150LM 830 IK10 WHT

Item No: 0049928




Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E [lm]	E [cd]	E [cd]
0.5	1.47	1474	56.8°	131
1.0	2.94	369	56.8°	33
1.5	4.41	164	56.8°	15
2.0	5.89	92	56.8°	8
2.5	7.36	59	56.8°	5
3.0	8.83	41	56.8°	4



START SURFACE IP66 1150LM 830 IK10 WHT

Item No: 0049928

SYLVANIA

General data

Product name	START SURFACE IP66 1150LM 830 IK10 WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor, Outdoor
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4579599
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	1150
Fixture luminous flux (lm)	1150
Luminaire efficacy (lm/W)	96
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Distribution type	Diffuse, Symmetric
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	12
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.83
Electrical protection	Class II
Control gear type	LED driver constant current
Dimming method	N/A
Inrush Current (A)	20
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	38
Max. products per 13A C Breaker	47
Max. products per 16A C Breaker	57
Max. products per 20A C Breaker	66
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B50	78000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	90
Nominal Product Diameter (mm)	300
Weight (kg)	0.78

START SURFACE IP66 1150LM 830 IK10 WHT

Item No: 0049928



Packaging

Product EAN number	5410288499284
Packaging single width (cm)	9.9
Packaging single depth (cm)	30.5
DUN14 (inner)	15410288499281
Packaging outer length / height (cm)	61.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40