

VKPK-26: Straight Entry Piece - Press Ø26 Black



Commercial information

Straight entry piece for Pro-Flow Manifold

Basic unit dimensions

Height	32 mm
Length	67 mm
Width	32 mm
Net weight	0.050 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Shape	Straight	Bend angle	90 Degrees
Model	1-part	Bend radius	0 Millimetre
Reducing	✘	Outer pipe diameter connection	26 Millimetre
Eccentric	✘	Length	66.6 Millimetre
System specific	✓	Wrench width	0 Millimetre
Main colour fitting	Black	Wrench width union nut	0 Millimetre
With buffer stud	✓	Medium temperature (continuous)	-10 70 Degrees celsius
High tensile strength	✘	Max. operating pressure at 20 °C	10 Bar
With thermal insulation	✘	Standard Dimension Ratio (SDR)	0
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
Certified according to NF 545	✘		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Gastec QA - AR 214 (H2)	✘		
Type approval according to BBR/EKS	✘		