


## 28PV-16041604-1: Double Backplate elbow female, build in 16x1/2"x16x1/2"



### Commercial information

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 37 mm    |
| Length     | 150 mm   |
| Width      | 69 mm    |
| Net weight | 0.355 kg |

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                             |              |                                  |                        |
|-----------------------------|--------------|----------------------------------|------------------------|
| System specific             | ✓            | Outer pipe diameter connection   | 16 Millimetre          |
| Housing material            | Brass        | Distance centre-to-centre        | 153 Millimetre         |
| Surface protection          | Untreated    | Max. operating pressure at 20 °C | 16 Bar                 |
| Connection                  | Press sleeve | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Contour code                | TH           |                                  |                        |
| With connection indicator   | ✗            |                                  |                        |
| With protective cap         | ✗            |                                  |                        |
| DVGW quality mark for gas   | ✗            |                                  |                        |
| DVGW quality mark for water | ✓            |                                  |                        |
| Compliant with NF 545       | ✗            |                                  |                        |
| KOMO certified              | ✓            |                                  |                        |