

## 17HNA-07-X: HN75 bracket connection R5/4" male inox



### Commercial information

The Super Size range includes the Henco multilayer pipe and Henco fittings with diameters of 75-90, with reducers to diameters of 32-40-50-63. The connectors ensure a complete multilayer pipe system with numerous variations for headers and risers. The many combination possibilities and the revolutionary connection technology make this modular system extremely flexible.

Like all Henco press fittings, the Super Size fittings come with leak detection and are made from high-performance plastic PVDF. These properties make the Henco Super Size fittings suited for different applications, such as drinking water installations, heating installations and installations in the chemical and food industries.

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 78 mm    |
| Length     | 44 mm    |
| Width      | 78 mm    |
| Net weight | 0.411 kg |

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Laboratory, Utility

## Technical characteristics

|                                    |  |                                 |                        |
|------------------------------------|--|---------------------------------|------------------------|
| Material connection 1              | Stainless steel                                | Bend radius                     | 0 Millimetre           |
| Material quality connection 1      | Stainless steel 316 L (1.4404)                 | Length                          | 44 Millimetre          |
| Surface protection connection 1    | Untreated                                      | Wrench width                    | 0 Millimetre           |
| Surface treatment connection 1     | Untreated                                      | Wrench width union nut          | 0 Millimetre           |
| Material connection 2              | Stainless steel                                | Tightening torque               | 0 0 Newtonmetre        |
| Material quality connection 2      | Stainless steel 316 L (1.4404)                 | Medium temperature (continuous) | -10 70 Degrees celsius |
| Surface protection connection 2    | Untreated                                      |                                 |                        |
| Surface treatment connection 2     | Untreated                                      |                                 |                        |
| Shape                              | Straight                                       |                                 |                        |
| Reducing                           | ✘  |                                 |                        |
| Eccentric                          | ✘  |                                 |                        |
| System specific                    | ✓  |                                 |                        |
| Connection 1                       | External thread cylindrical BSPP-G (ISO 228-1) |                                 |                        |
| Nominal diameter connection 2      | 1 1/4 inch (32)                                |                                 |                        |
| Main colour fitting                | Grey   |                                 |                        |
| With buffer stud                   | ✘  |                                 |                        |
| With thermal insulation            | ✘  |                                 |                        |
| With sealing rings/gaskets         | ✘  |                                 |                        |
| Capped                             | ✘  |                                 |                        |
| With connection indicator          | ✘  |                                 |                        |
| With drain valve                   | ✘  |                                 |                        |
| With de-aerator                    | ✘  |                                 |                        |
| FM quality mark                    | ✘  |                                 |                        |
| LPCB quality mark                  | ✘  |                                 |                        |
| ULC quality mark                   | ✘  |                                 |                        |
| UL quality mark                    | ✘  |                                 |                        |
| DIN-CERTCO certificate             | ✘  |                                 |                        |
| VdS quality mark                   | ✘  |                                 |                        |
| With approval for TÜV              | ✘  |                                 |                        |
| DVGW quality mark for gas          | ✘  |                                 |                        |
| DVGW quality mark for water        | ✘  |                                 |                        |
| KIWA certified                     | ✘  |                                 |                        |
| Gastec QA mark                     | ✘  |                                 |                        |
| KOMO certified                     | ✘  |                                 |                        |
| Type approval according to BBR/EKS | ✘  |                                 |                        |