

# Specifications

Photo is representative

## Eaton S811+R13P3S

Eaton S811+ soft starter, Soft Starter ,110 mm, 135 A, Pimp control with OPT Inside delta

### General specifications

<b>PRODUCT NAME</b>	Eaton S811+ soft starter
<b>CATALOG NUMBER</b>	S811+R13P3S
<b>UPC</b>	786685558967
<b>PRODUCT LENGTH/DEPTH</b>	13 in
<b>PRODUCT HEIGHT</b>	10 in
<b>PRODUCT WIDTH</b>	9.5 in
<b>PRODUCT WEIGHT</b>	12.5 lb
<b>CERTIFICATIONS</b>	Contact Manufacturer
<b>PRODUCT TYPE</b>	Soft starter



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	42-135A
<b>SPECIAL FEATURES</b>	30 second ramp or 450% current limit at 50°C, inside-the-delta connection, pump control and extended ramp functions
<b>TYPE</b>	Premium
<b>FRAME SIZE</b>	R
<b>RATING</b>	30 kW at 230 V, 55 kW at 380-400 V, 59 kW at 440 V

## Resources

CATALOGS	<a href="#">Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1</a> <a href="#">Product Range Catalog Drives Engineering</a>
MULTIMEDIA	<a href="#">Soft Starter Product Family Overview</a> <a href="#">Soft starter DS7 up to 200 A</a> <a href="#">Soft Starter DS7 up to 32 A</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - S811+R13P3S</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

