

## 36PG-2015P: Press adapter to copper press Gas 20x15



### Commercial information

The fittings are equipped with a special O-ring, This O-ring is made of the material HNBR and is resistant to gas.

- Press transition from copper to Henco press
- Faster and more secure processing due to press connection on the copper side as opposed to a compression connection.
- Copper side suitable for M --, V and SA profile press jaws
- Allowed for use in hard-to-reach places
- Coupling may be collapsed if packed protectively Alloy
- CW617
- Compatible with thin-walled steel, copper and inox

#### Basic unit dimensions

Height	26 mm
Length	55 mm
Width	26 mm
Net weight	0.069 kg

#### Certificates

GASTEC, DVGW Gas

#### Applications

Gas

#### Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Surface treatment connection 1	Untreated	Length	55 Millimetre
Material connection 2	Brass	Wrench width	0 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Wrench width union nut	0 Millimetre
Surface protection connection 2	Untreated	Medium temperature (continuous)	-10 60 Degrees celsius
Surface treatment connection 2	Untreated	Max. operating pressure at 20 °C	10 Bar
Shape	Straight	Standard Dimension Ratio (SDR)	0
Reducing	✘		
Eccentric	✘		
System specific	✓		
Connection 1	Press sleeve		
Contour code connection 1	TH		
Connection 2	Press sleeve		
Contour code connection 2	M/F (seal) (expired)		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✓		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✓		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		