

Walraven BISOFIX® E19 + 2S

(D0316)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- clamp: zinc plated
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fo,z
Unit description	mm		mm	mm	mm	mm	N
I193303012	12	M8/M10	74	84	50	19.3	100
I193303015	15	M8/M10	83	93	50	19.5	100
I193303018	17.2 - 18	M8/M10	83	93	50	19.3	100
I193303022	21.3 - 22	M8/M10	83	93	50	19.3	100
I193303028	26.9 - 28	M8/M10	89	99	50	19.3	100
I193303035	33.7 - 35	M8/M10	103	118	50	19.3	100
I193303042	42.4	M8/M10	103	118	50	19.3	150
I193303048	48.3	M8/M10	119	136	50	19.3	225
I193303054	54	M8/M10	127	143	50	23	225
I193303057	57	M8/M10	127	143	50	23	225
I193303060	60.3	M8/M10	127	143	50	19.9	350
I193303064	64	M8/M10	136	153	50	25.3	350
I193303070	70	M8/M10	151	168	50	27.3	452
I193303076	76.1	M8/M10	151	168	50	25.3	575
I193303089	88.9	M8/M10	168	185	50	25.3	875
I193303102	101.6	M8/M10	177	194	50	25.3	1,000
I193303108	108	M8/M10	186	203	50	25.3	1,075
I193303114	114.3	M8/M10	199	217	50	25.3	1,250
I193303133	133	M8/M10	221	239	100	26.2	1,475
I193303140	139.7	M8/M10	221	239	100	25.3	1,700
I193303160	159 - 160	M8/M10	243	260	100	25.3	1,950
I193303168	168.3	M8/M10	253	271	100	25.3	2,125