

# Specifications

Photo is representative

## Eaton 064978

Eaton Moeller® series P1 Main switch, P1, 32 A, rear mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series P1 Main switch
<b>CATALOG NUMBER</b>	064978
<b>MODEL CODE</b>	P1-32/V/SVB-SW/N/HI11
<b>EAN</b>	4015080649786
<b>PRODUCT LENGTH/DEPTH</b>	90 mm
<b>PRODUCT HEIGHT</b>	70 mm
<b>PRODUCT WIDTH</b>	78 mm
<b>PRODUCT WEIGHT</b>	0.287 kg
<b>WARRANTY</b>	Not Applicable
<b>CERTIFICATIONS</b>	IEC/EN 60947 IEC/EN 60947-3 VDE 0660 UL UL 60947-4-1 CSA File No.: 012528 IEC/EN 60204 CSA Class No.: 3211-05 CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NLRV UL File No.: E36332 CE CSA CSA-C22.2 No. 94
<b>CATALOG NOTES</b>	Rated Short-time Withstand Current (Icw) for a time of 1 second
<b>GLOBAL CATALOG</b>	064978

## Product specifications

<b>PRODUCT CATEGORY</b>	Main switch
<b>FEATURES</b>	Version as maintenance-/service switch Version as main switch
<b>ACTUATOR COLOR</b>	Black
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	UV resistance only in connection with protective shield.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF</b>	Does not apply, since the

<b>PROTECTION OF ASSEMBLIES</b>	entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	Black rotary handle and locking ring
<b>OPERATING FREQUENCY</b>	1200 Operations/h
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>RATED PERMANENT CURRENT AT AC-21, 400 V</b>	32 A
<b>RATED PERMANENT CURRENT AT AC-23, 400 V</b>	32 A
<b>RATED UNINTERRUPTED CURRENT (IU)</b>	32 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>SWITCHING POWER AT 400 V</b>	15 kW
<b>RATED OPERATIONAL POWER AT AC-3, 500 V, 50 Hz</b>	18.5 kW
<b>DEVICE CONSTRUCTION</b>	Built-in device fixed built-in technique

<b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>	0.64 kA 640 A, Contacts, 1 second
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>MOUNTING POSITION</b>	As required
<b>ACTUATOR TYPE</b>	Door coupling rotary drive
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 115/120 V, 60 HZ, 1-PHASE</b>	1 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 200/208 V, 60 HZ, 1-PHASE</b>	2 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 200/208 V, 60 HZ, 3-PHASE</b>	3 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 230/240 V, 60 HZ, 1-PHASE</b>	3 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 230/240 V, 60 HZ, 3-PHASE</b>	7.5 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 460/480 V, 60 HZ, 3-PHASE</b>	10 HP
<b>ASSIGNED MOTOR</b>	
<b>POWER AT 575/600 V, 60 HZ, 3-PHASE</b>	15 HP
<b>EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID</b>	1.8 W
<b>NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY</b>	1

<b>CLOSED CONTACTS)</b>	
<b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT</b>	80 kA
<b>(IQ)</b>	
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP65
<b>NUMBER OF POLES</b>	4
<b>MOUNTING METHOD</b>	Rear mounting
<b>DEGREE OF PROTECTION</b>	NEMA 12
<b>SUITABLE FOR</b>	Branch circuits, suitable as motor disconnect, (UL/CSA)
<b>LOCKING FACILITY</b>	Lockable in the 0 (Off) position
<b>FUNCTIONS</b>	STOP function Interlockable
<b>NUMBER OF SWITCHES</b>	1
<b>SAFE ISOLATION</b>	440 V AC, Between the contacts, According to EN 61140
<b>SCREW SIZE</b>	M4, Terminal screw
<b>SHOCK RESISTANCE</b>	15 g, Mechanical, According to IEC/EN 60068-2-27, Half- sinusoidal shock 20 ms
<b>LIFESPAN, MECHANICAL</b>	300,000 Operations
<b>LOAD RATING</b>	$2 \times I_e$ (with intermittent operation class 12, 25 % duty factor) $1.3 \times I_e$ (with intermittent operation class 12, 60 % duty factor) $1.6 \times I_e$ (with intermittent operation class 12, 40 % duty factor)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	10A, IU, (UL/CSA)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	A600 (UL/CSA) P600 (UL/CSA)
<b>TERMINAL CAPACITY</b>	2 x (1.5 - 6) mm <sup>2</sup> , solid or stranded 14 - 8 AWG, solid or flexible with ferrule 1 x (1 - 4) mm <sup>2</sup> , flexible

	with ferrules to DIN 46228 2 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228 1 x (1.5 - 6) mm <sup>2</sup> , solid or stranded
<b>SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)</b>	30 A, Rated uninterrupted current max. (UL/CSA)
<b>SAFETY PARAMETER (EN ISO 13849-1)</b>	B10d values as per EN ISO 13849-1, table C.1
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	1
<b>NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V</b>	3
<b>NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V</b>	1
<b>NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V</b>	2
<b>NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V</b>	2
<b>RATED BREAKING CAPACITY AT 220/230 V (COS PHI TO IEC 60947-3)</b>	260 A
<b>RATED BREAKING CAPACITY AT 400/415 V (COS PHI TO IEC 60947-3)</b>	300 A
<b>RATED BREAKING CAPACITY AT 500 V (COS PHI TO IEC 60947-3)</b>	290 A
<b>RATED BREAKING CAPACITY AT 660/690 V (COS PHI TO IEC 60947-3)</b>	250 A
<b>RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)</b>	320 A
<b>RATED OPERATING VOLTAGE (UE) - MAX</b>	690 V
<b>RATED OPERATING VOLTAGE (UE) - MIN</b>	690 V
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	690 V
<b>SHORT-CIRCUIT CURRENT RATING (BASIC RATING)</b>	5 kA, SCCR (UL/CSA) 110A, max. Fuse, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT)</b>	50 A, Class J, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA)
<b>SHORT-CIRCUIT</b>	50 A gG/gL, Fuse, Contacts

---

**PROTECTION RATING**

**RATED OPERATIONAL**

CURRENT (IE) AT AC-21, 32 A  
440 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-23A, 32 A  
230 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-23A, 32 A  
400 V, 415 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-23A, 30 A  
500 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-23A, 19.8 A  
690 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-3, 26.4 A  
220 V, 230 V, 240 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-3, 26.4 A  
380 V, 400 V, 415 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-3, 23.4 A  
500 V

**RATED OPERATIONAL**

CURRENT (IE) AT AC-3, 14.7 A  
660 V, 690 V

**RATED OPERATIONAL**

CURRENT (IE) AT DC-1, 32 A  
LOAD-BREAK SWITCHES  
L/R = 1 MS

**RATED OPERATIONAL**

CURRENT (IE) AT DC-23A, 12 A  
120 V

**RATED OPERATIONAL**

CURRENT (IE) AT DC-23A, 25 A  
24 V

**RATED OPERATIONAL**

CURRENT (IE) AT DC-23A, 25 A  
48 V

**RATED OPERATIONAL**

CURRENT (IE) AT DC-23A, 25 A  
60 V

**RATED OPERATIONAL**

CURRENT FOR SPECIFIED 32 A  
HEAT DISSIPATION (IN)

**RATED OPERATIONAL**

POWER AT AC-23A, 7.5 kW  
220/230 V, 50 Hz

**RATED OPERATIONAL**

POWER AT AC-23A, 400 V, 15 kW  
50 Hz

**RATED OPERATIONAL**  
**POWER AT AC-23A, 500 V, 18.5 kW**  
**50 HZ**

**RATED OPERATIONAL**  
**POWER AT AC-23A, 690 V, 15 kW**  
**50 HZ**

**RATED OPERATIONAL**  
**POWER AT AC-3, 380/400 13 kW**  
**V, 50 HZ**

**RATED OPERATIONAL**  
**POWER AT AC-3, 415 V, 50 13 kW**  
**Hz**

**RATED OPERATIONAL**  
**POWER AT AC-3, 690 V, 50 15 kW**  
**Hz**

**HOUSING COLOR** Black

**HOUSING MATERIAL** Plastic

## Resources

**BROCHURES** [Brochure - T Rotary Cam switch and P Switch-disconnector](#)

**CATALOGS** [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

**DECLARATIONS OF CONFORMITY** [eaton-main-switch-declaration-of-conformity-uk251289en.pdf](#)

**DECLARATIONS OF CONFORMITY** [eaton-main-switch-declaration-of-conformity-eu250806en.pdf](#)

[eaton-rotary-switches-mounting-p1-main-switch-dimensions-002.eps](#)

[eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps](#)

**DRAWINGS** [eaton-rotary-switches-mounting-p1-main-switch-3d-drawing-002.eps](#)

[eaton-general-mounting-p1-main-switch-symbol-002.eps](#)

[eaton-rotary-switches-t0-main-switch-symbol.eps](#)

**ECAD MODEL** [ETN.064978.edz](#)

**INSTALLATION INSTRUCTIONS** [eaton-switch-disconnector-p1-rear-mounting-ii03802004z.pdf](#)

**INSTALLATION VIDEOS** [Eaton's P Switch-disconnectors used in a factory](#)

**MCAD MODEL** [eaton-p1\\_v\\_svbn\\_hi11-drawing.dwg](#)

[eaton-p1\\_v\\_svbn\\_hi11-3d-model.stp](#)

**PRODUCT NOTIFICATIONS** [MZ008006ZU\\_Orderform\\_Customized\\_Switch.pdf](#)

[MZ008005ZU\\_Orderform\\_Customized\\_Switch.pdf](#)

**SPECIFICATIONS AND** [Eaton Specification Sheet - 064978](#)

**DATASHEETS****WIRING  
DIAGRAMS**

[eaton-rotary-switches-main-switch-p1-main-switch-wiring-diagram.eps](#)

**PROJECT NAME:****PROJECT NUMBER:****PREPARED BY:****DATE:**

**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

