

Product data sheet

Item No. 92.230.1004.1

Cable assembly GST18I3K1-S 75 10SW

geis® Connection cable male - free end; length: 1m; type GST18I3; 3-pole; 250 V / 6 A; colour of coding: black with black strain-relief; cable: H05VV-F 3G0,75, colour: black



Item No.	92.230.1004.1
EAN	4015573791626
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	6 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	0.75 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	6.7 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

0,2m ± 3% entspricht 92.230.0204.F
 0,2m ± 3% equivalent to 92.230.0204.F

9,9m ± 3% entspricht 92.230.9904.F
 9,9m ± 3% equivalent to 92.230.9904.F

Ansicht "X"
 view "X"

Teil-Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:	Teil-Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:	Teil-Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:
92.230.0204.F	schwarz / black	186	92.230.3504.F	schwarz / black	3486			
92.230.0304.F	schwarz / black	286				92.230.7004.F	schwarz / black	6986
92.230.0404.F	schwarz / black	386						
92.230.0504.F	schwarz / black	486						
92.230.0604.F	schwarz / black	586						
92.230.0704.F	schwarz / black	686	92.230.4004.F	schwarz / black	3986			
92.230.0804.F	schwarz / black	786						
92.230.0904.F	schwarz / black	886						
92.230.1004.F	schwarz / black	986						
92.230.1104.F	schwarz / black	1086						
92.230.1204.F	schwarz / black	1186	92.230.4504.F	schwarz / black	4286			
92.230.1304.F	schwarz / black	1286						
92.230.1404.F	schwarz / black	1386				92.230.8004.F	schwarz / black	7986
92.230.1504.F	schwarz / black	1486						
92.230.1604.F	schwarz / black	1586						
92.230.1704.F	schwarz / black	1686	92.230.5004.F	schwarz / black	4986			
92.230.1804.F	schwarz / black	1786						
92.230.1904.F	schwarz / black	1886						
92.230.2004.F	schwarz / black	1986						
92.230.2104.F	schwarz / black	2086						
92.230.2204.F	schwarz / black	2186						
92.230.2304.F	schwarz / black	2286						
92.230.2404.F	schwarz / black	2386				92.230.9004.F	schwarz / black	8986
92.230.2504.F	schwarz / black	2486						
92.230.2604.F	schwarz / black	2586						
92.230.2704.F	schwarz / black	2686	92.230.6004.F	schwarz / black	5986			
92.230.2804.F	schwarz / black	2786						
92.230.2904.F	schwarz / black	2886						
92.230.3004.F	schwarz / black	2986						

Typ: GST18i3K1-S 75 . SW

Freiheiten nach /	Meßtisch /	Marktort und Oberflächen /	2000 /	Tag /	Name /	1. Bewertung /	30.1 /	re 1 /
/	/	/	12.09.11 /	13.09.11 /	Reinle /	T /	92.230.0204.1 01K /	0 /
/	/	/	10.09.2004 /					
bestenfalls /	Beleg /	Stell /	wieland		INST_STECKVERB_M_KABEL			
Änderung		Elektronische Verbindungen		Stecker/male-free end Cable/Free end 6,75mm/64		Install. coupler		