



Features

- 50,000 hours average rated life Last 2.5 times longer than 600mm 18W fluorescent T8 Tri-phosphor lamp
- High switching cycles – 200,000X
- High lumen efficacy - 147lm/W
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Works only with compatible electronic ballast
- Must replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballast
- Suitable for direct mains operation (AC 220-240V) with single-end AC input
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Product Overview

Product name	ToLEDo Superia T8 Universal V3 2FT 1100LM 865
Technology	LED
Watt (Rated) (W)	7.5
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	160
Photobiological Risk Group	RG0
Wattage (W)	7.5
Power consumption (W)	7.5

ToLEDo Superia T8 Universal V3 2FT 1100LM 865 0029274

Dimmable	No
Average life (Nominal) (h)	50000
Housing colour	White
IP rating	IP20
Product EAN number	5410288292748
Warranty	5 years
Useful luminous flux (#use)	1100

Technical drawings

