

Accessories for pluggable interface relays CR-U

Sockets

Data sheet

2CDC 291 043 F0004




CR-U2S

2CDC 291 044 F0004



CR-U3S

2CDC 292 082 F0004



CR-UH

Features

- Standard socket for interface relays CR-U
- Snap-on mounting on DIN rail
- Width 38 mm
- Connector for pluggable function modules: reverse polarity protection, LED indication, RC element, overload protection

Approvals



Marks



Ordering data

Type	Version	Order code
Sockets		
CR-U2S	Socket for 2 c/o + module	1SVR 405 670 R0000
CR-U3S	Socket for 3 c/o + module	1SVR 405 660 R0000
CR-U3E	Socket for 3 c/o	1SVR 405 660 R0100
Socket accessories		
CR-UH	Holder for CR-U socket	1SVR 405 669 R0000

Packing unit = 10 pieces.

Relays and pluggable function modules see separate data sheets.

Technical data

Type		CR-UxS	CR-U2E
Output circuits		11-12/14, 21-22/24, ...	
Number of poles		2 or 3	2
Rated voltage	10 A	400 V AC	
	12 A	300 V AC	-
Rated current		10 A / 12 A	10 A
General data			
Dimensions (without holder)	(L x W x H)	75 x 38 x 26 mm	70 x 38 x 26 mm
Weight			
Mounting position			
Degree of protection	terminals	IP 20 B (EN 60529)	
Temperature range	operation	-40 °C ... +85 °C	
	storage		
Wire size	rigid flexibel	2 x 2.5 mm ² (2 x 14 AWG)	
	with wire end ferule	2 x 1.5 mm ² (2 x 16 AWG)	
Torque		0.8 Nm	
Mounting		DIN rail (EN 50022)	
Material	socket	PA 6+FV -V2	PA 6+GF - V2
	contacts	CuZn33	
	contact surface	6µ nickelised	
	terminals	8 µ galvanized	
	combi screw M3	8.8 Steel, 5µ nickelized	
Isolation data			
Insulation voltage		< 3 kV	
Isolation between coil and contacts		VDE 0106 / 101	
Clearance and creepage distance		C250, VDE 0110b / 2.79	

Accessories for pluggable interface relays CR-U


Sockets

Data sheet

Technical data (continued)

Type	CR-Mxss	CR-MxLS
Standards		
Product standard	EN 61984: 2001	
Low Voltage Directive	73/23/EEC	
Approvals / marks		
Approvals	RU(UL), cRUus), CSA, GOST	
Marks	CE	


Position of connection terminals



2CDC 292 077 F0004

CR-U2S


A1-A2 Supply voltage
11-12/14 Relay outputs
21-22/24



2CDC 292 078 F0004

CR-U3S

A1-A2 Supply voltage
11-12/14 Relay outputs
21-22/24
31-32/34




2CDC 292 080 F0004

CR-U2E



A1-A2 Supply voltage
11-12/14 Relay outputs
21-22/24

Dimensions

in mm





CR-UxS



2CDC 292 079 F0004

CR-U2E



2CDC 292 081 F0004

Accessories

Relays: see data sheet 2CDC 117 003 D02xx
Pluggable function modules: see data sheet 2CDC 117 008 D02xx



ABB STOTZ-KONTAKT GmbH

Eppelheimer Straße 82 69123 Heidelberg, Germany

Postfach 10 16 80 69006 Heidelberg, Germany

Internet www.abb.de/epr

E-Mail epr-support@stotzkontakt.de