

## Product data sheet

Item No. 92.232.0503.5

### Cable assembly

geis® Connection cable female - free end; length: 0,5m; type GST18I3; 3-pole; 250 V / 16 A; colour of coding: red with red strain-relief; cable: H05VV-F 3G1,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 92.232.0503.5 |
| EAN        | 4015573734081 |
| Order Unit | 100 Piece(s)  |

### Certificates / Approvals



### Technical data

#### General

|                                          |             |
|------------------------------------------|-------------|
| Rated current                            | 16 A        |
| Rated voltage                            | 250 V       |
| Rated impulse voltage                    | 4 kV        |
| Pollution degree                         | 2           |
| Mechanical coding                        | Code 3      |
| Interlockable                            | Yes         |
| Color of coding/ contact carrier         | Salmon pink |
| Marking of poles                         |             |
| Color of housing inclusive strain relief | Salmon pink |

#### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 3                                   |
| Nominal cross section conductor | 1.5 mm <sup>2</sup>                 |
| Degree of protection (IP)       | IP40                                |
| Wire strip length               | 9 mm                                |
| sheath strip length             | 37 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H05VV-F                             |

|                     |                   |
|---------------------|-------------------|
| Cable colour        | Black             |
| Cable diameter      | 8.3 mm            |
| Version of cable    | Female - free end |
| Type of cord set    | Connection cable  |
| Version cable end 1 | GST18i3 socket    |
| Version cable end 2 | Free end          |

#### Material

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | No         |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

#### Dimensions

|              |       |
|--------------|-------|
| Total length | 0.5 m |
|--------------|-------|

#### Technical drawing

