

WBS-1604-BL: Wall box 1x blue 1/2"Fx16mm compression



Commercial information

Wall box

- High-quality corrosion-proof built-in box made of plastic.
- Box in a neutral colour with a blue and red cover } Small dimensions for easy grinding (95x33x40 mm).
- Can also be easily combined with drywalls on steel profiles.
- Homogeneous closure for installation in masonry or plastering.
- Fitted with a groove to hold the pipe sleeve in place and ensure connection to the pipe. The built-in box can be opened quickly and easily.
- The pipe and coupling can be easily accessed without damaging the wall.
- Suited for heating and sanitary applications.
- Corrosion-proof, for a perforated steel mounting bracket.

 Inter-axis distances of 40, 50, 80, 120 and 153 mm, indicated on the mounting bracket.
- Ready for all common H-blocks and sanitary faucets.
- Handy mounting rail available as accessory for hollow drywalls or floor levelling screeds. Available in 16 and 20 mm press fitting and 16 mm screw fitting.

Basic unit dimensions		
Height	45 mm	
Length	97 mm	
Width	40 mm	
Net weight	0.142 kg	

Certificates

KIWA, KOMO, ATG, ÖN EN 21003-2/-3, ÖVGW Wasser, ETA, WRAS, GOST-R, PZH, ITC, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Building installations, Industry, Utility, Shipbuilding



Technical characteristics

Housing material	Brass	Medium temperature (continuous)	-10 70 Degrees celsius
Surface protection	Untreated	Max. operating pressure at 20 °C	10 Bar
Shape	Right-angled		
Thread size	1/2 inch		
System specific	✓		
Nominal diameter connection 1	DN 12		
Connection	Press sleeve		
Contour code	TH		
KIWA certified	✓		

