

Motion detector, 230 V, 14 m, round, for flush-mounting box, white

351-25340



4 year warranty



230 V



stand-alone



IP20



N.O. (max. 10 A)



5 lx – 2,000 lx



360°



14 m from a height of 3 m



2 m – 6 m




flush-mounting box





Detection range



H	A Across	B Towards
		
2 m	Ø 10 m	Ø 5 m
2.5 m	Ø 12 m	Ø 6 m
3 m	Ø 14 m	Ø 7 m
3.5 m	Ø 16 m	Ø 8 m
4 m	Ø 16 m	Ø 8 m
5 m	Ø 16 m	Ø 8 m
6 m	Ø 16 m	Ø 8 m

The motion detector with one channel for flush mounting in ceilings is suitable for switching indoor lighting on and off. You can always activate the light with a N.O. push button (230 Vac) (to be ordered separately). The detector is equipped with an integrated light sensor.

Colour: white

- Ideal for all standard applications (walking areas), such as stairwells, basements, underground garages, etc.
- Very good price/quality for standard applications


Technical features

Configuration	stand-alone
Input voltage	230 Vac
Detector output	230 V (ON/OFF)
Maximum current consumption	3.91 mA
Switch-off delay	pulse, 10 s – 20 min
Maximum power consumption	0.9 W
Maximum MCB rating	10 A
Detection angle	360 °
Detection range (PIR)	14 m from a height of 3 m
Minimum ambient temperature	-20 °C
Maximum ambient temperature	+40 °C
Mounting method	flush-mounting box
Mounting height	2 m – 6 m
Colour	white
Dimensions visible (HxWxD)	105 mm x 105 mm
Dimensions (HxWxD)	105 mm x 105 mm x 71 mm
Protection degree standalone	IP20
Impact resistance	IK02
Modification of settings	Potentiometers or IR remote control
Certificates marks	CE

Accessories

351-25420	Surface-mounting box, round, white
350-41936	Universal remote control for smartphone
351-25320	IR remote control
351-25310	IR remote control for users

Dimensions



Wiring diagram

