


INSAVER U19 IP44 175 1150LM 830 PIR

Item No: 0030518


SYLVANIA

PRO




Technical Assets

Dimensions (mm)



Photometrics

Beam Angle (°)	Beam Diameter (mm)	Beam Area (mm²)	Beam Area (ft²)	Beam Area (sq ft)
8.3	67.5	3571	0.039	0.044
10	80	6317	0.068	0.074
15.8	142	20164	0.218	0.235
22.5	212	44976	0.486	0.524
30	281	78881	0.853	0.917
37.5	351	123201	1.334	1.441
45	420	176400	1.913	2.067
52.5	490	240100	2.590	2.791
60	560	313600	3.377	3.637
67.5	630	396900	4.274	4.594
75	700	490000	5.281	5.721
82.5	770	592900	6.398	6.921
90	840	705600	7.625	8.211



INSAVER U19 IP44 175 1150LM 830 PIR

Item No: 0030518

SYLVANIA

General data

Product name	INSAVER U19 IP44 175 1150LM 830 PIR
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4278517
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	1150
Fixture luminous flux (lm)	1150
Luminaire efficacy (lm/W)	121
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	70
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	9.5
Primary Supply/Product voltage - min (V)	220.0
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimming method	N/A
Drive current (mA)	300
Inrush Current (A)	15
Inrush Duration (µs)	104
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	66
Max. products per 16A C Breaker	96
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L70 B10	100000
Lifespan L80 B50	100000
Lifespan L80 B20	88000
Lifespan L80 B10	80000
Lifespan L90 B50	50000
Lifespan L90 B20	43000
Lifespan L90 B10	39000

INSAVER U19 IP44 175 1150LM 830 PIR

Item No: 0030518

SYLVANIA

Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Not Applicable
Nominal Product Height (mm)	50
Nominal Product Diameter (mm)	195
Built-in diameter (mm)	175
Weight (kg)	0.913

Packaging

Product EAN number	5410288305189
Packaging single width (cm)	25.5
Packaging single depth (cm)	8.5
DUN14 (inner)	15410288305186
Packaging outer length / height (cm)	52.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40