Technical data sheet

Installation frame for combination of 2x and 2x Modul 45® devices
Item number: 7408682



For the installation of a combination of double and double Modul 45 sockets for System 55 service outlets with mounting support for vertical installation of Modul 45 devices. The installation frame is designed for use with 0° sockets for straight connectors (not angled connectors).

CE

PC/ABS Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

Item number	7408682
Type	MT45V 2+2
Description 1	Installation frame
Description 2	for 2f + 2f Modul 45
Manufacturer	OBO
Colour	Graphite black; RAL 9011
Material	Polycarbonate/Acrylnitrile-butadiene-styrene
Smallest sales unit	5
Unit of quantity	Piece
Weight	0.9 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,0613 kg CO2e / 1 Piece

Technical data sheet

Installation frame for combination of 2x and 2x Modul 45® devices
Item number: 7408682

Dimensions



Technical data

Number of installable devices	2
Floor plate	no
Seal installation option	no
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	yes
Suitable for screed-covered underfloor ducts	yes
Suitable for cavity floor installation	yes
Suitable for underfloor ducts	yes
Accessory mounting type	Lock
ROHS-conformant	yes
Strain relief option	yes