

## Data Sheet | Item Number: 281-418

Test plug module; modular; suitable for all WAGO 281, 776, 777 and 781 series rail-mounted terminal blocks with jumper slots in the current bar; gray

<https://www.wago.com/281-418>



Color: ■ gray

### Notes

Safety Information

These test plugs are not suitable for Ex e applications.

### Electrical data

#### General information

Test voltage	400 V
Test current	6 A

### Physical data

Width	6 mm / 0.236 inches
Module width	6 mm / 0.236 inches

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.022 MJ
Weight	1.9 g

**Commercial data**

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918276320
Customs tariff number	85366990990

**Product Classification**

UNSPSC	39121410
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 9.0	EC002255
ETIM 10.0	EC002255
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

<b>Compliance Search</b>	
Environmental Product Compliance 281-418	<a href="#">↓</a>

**Documentation**

<b>Bid Text</b>			
281-418	19.02.2019	xml 2.88 KB	<a href="#">↓</a>
281-418	28.04.2017	doc 23.50 KB	<a href="#">↓</a>

**CAD/CAE-Data**

<b>CAD data</b>	
2D/3D Models 281-418	<a href="#">↓</a>

<b>CAE data</b>	
WSCAD Universe 281-418	<a href="#">↓</a>

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Test and measurement

##### 1.1.1.1 Testing accessories



**Item No.: 210-136**

Test plug; 2 mm Ø; with 500 mm cable; red


## Installation Notes

### Installation



Snapping test plug and spacer modules together to assemble a multipole test plug module.

## Testing



Test plug modules are directly plugged into the jumper contact slot of the current bar.