

UFH-P18-GP10: Gypsum fibreboard 10mm,flat for RENO12 system



Commercial information

Basic unit dimensions

| Dasic unit uniclisions | | |
|------------------------|-----------|--|
| Height | 10 mm | |
| Length | 1,500 mm | |
| Width | 1,000 mm | |
| Net weight | 18.000 kg | |

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility



Technical characteristics

| Edge finishing long side | Other | Length | 1500 Millimetre |
|--|-------|-----------|------------------------------|
| Edge finishing head end | Other | Width | 1000 Millimetre |
| Colour visible surface | White | Thickness | 10 Millimetre |
| Suitable for floor | ✓ | Weight | 18 Kilogram per square metre |
| Suitable for ceiling mounting | × | | |
| Suitable for damp space | ✓ | | |
| With insulation | × | | |
| Fire retardant impregnated | × | | |
| Suitable as plasterboard | × | | |
| With perforation | × | | |
| With decorative finish | × | | |
| Lead insert | × | | |
| Bendable | × | | |
| Suitable for fire protection of load-bearing constructions | × | | |
| Fixing | × | | |
| Suitable for outdoor application | × | | |
| Suitable for protection from radiation | × | | |
| Factory bent board | × | | |
| Glass-fibre reinforced | × | | |
| Fleece reinforced | × | | |

