


VEK-060510-Z: Manifold 1 with "3/4" male threaded outlets for eurocone, 1" 10x3/4" EK



Commercial information

Messing verdeler 1" zonder ontluuchtingsopening met aantal euroconus aansluitingen

Basic unit dimensions

Height	58 mm
Length	503 mm
Width	38 mm
Net weight	2.650 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	10
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	50 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	38 Millimetre
Mounting method	Surface mounting	Height	58 Millimetre
Model	Distributor/collector	Depth	30 Millimetre
Material	Brass	Length distributor	503 Millimetre
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Nominal diameter connection 2	1 inch (25)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	3/4 inch (20)		
Connection branches	Euroconus standardless		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✗		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		