

Product data sheet

Item No. 96.454.8004.6

Cable assembly RST20i5KS-S 40P 80TB04

Connection cable, male - free end, length 8m, RST20i5, 5 pole, mains 250V/dimming, 20A, cable type H05VV, cross section 4,0 mm², color of coding: turquoise



Item No.	96.454.8004.6
EAN	4015573943025
Order Unit	3 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black



Cable diameter	14.3 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	8 m
--------------	-----

Technical drawing

Kabeltype/cable type H05VV-F5G4,0

Teil-Nr. part-no.	L	Beispiel (Farbe: türkisblau) example (colour: turquoiseblue)	Typ type
96.454.XX04.6	XX in dm-Schritten	96.454.1004.6 = 104m/L= 1000mm	RST2015KS-S 40P T0TB04
96.454.XX04.6	XX in m-Schritten	96.454.12004.6 = 12 m/L=12000mm	RST2015KS-S 40P X12TB04

96.454.1004.6	01K	a
---------------	-----	---

KONFEKT_LEITUNG
 Schraubklemme ohne Ø abwärts/terminal connector without screw
 96.454.1004.6
 01K a