


Features

- Excellent fragment retention in the event of breakage. The protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakage. The 97% UV-A transmission of FEP maintains maximum insect attraction.

Product Overview

Product name	F20W T12 BL368 24 Toughcoat™
Technology	Special applications
Cap/Base	G13
Fixture rating	Enclosed
E-number FI	4940431
Wattage (W)	20.00
Product EAN number	5410288001258

Technical drawings



Data table

GENERAL DATA

Product name	F20W T12 BL368 24 Toughcoat™
Technology	Special applications
Cap/Base	G13
Fixture rating	Enclosed
Operating temperature range (°C)	-20°C...+40°C
E-number FI	4940431

OPTICAL DATA

Ambient temperature for maximum luminous flux (°C)	25
Adjustable chromaticity	N

ELECTRICAL DATA

Wattage (W)	20.00
Primary Supply/Product voltage - min (V)	220
Control gear required	No

PHYSICAL DATA

Nominal Product Length (mm)	600.0
Nominal Product Diameter (mm)	38
Max. Length base to base (mm) - A	589.8
Length base to pin Min-Max (mm) - B	594.5-596.9
Max. Lamp Length (mm) - C/L	604.0
Max. Lamp Diameter (mm) - D	40.5
Weight (kg)	0.201

PACKAGING

Single packaging type	Carton
Product EAN number	5410288001258
Packaging single width (cm)	4.3
Packaging single depth (cm)	4.1

F20W T12 BL368 24 Toughcoat™ 0000125

DUN14 (outer)	15410288001255
----------------------	----------------

Packaging outer length / height (cm)	63.0
---	------

SAFETY DATA

Lamp mercury content (mg)	9.00
----------------------------------	------

Optimal operating condition (°C)	-20-40
---	--------

Breakage cleaning instructions	Applicable
---------------------------------------	------------

Recommendation for disposal at end of life	Applicable
---	------------

Special purpose lamp	Yes
-----------------------------	-----

Intended purpose	Flykilling - Insect attraction
-------------------------	--------------------------------

Dry applications use only	No
----------------------------------	----

Suitable for household illumination	No
--	----

Safety message	Not suitable for household
-----------------------	----------------------------