

### Features

- A bright, all-around lighting solution for living rooms, wall lights, ceiling lights, compact and decorative luminaires Quick and easy replacement of compact fluorescent, halogen or incandescent lamp 15,000H average rated life 85% energy savings compared to incandescent Last 50% longer and consume 45% less energy compared to compact fluorescent integrated lamps Omni-directional light distribution Non-dimmable



### Product Overview

Product name	ToLEDo Stick V4 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	5.0
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740964
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	5.0
Power consumption (W)	5
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295589

## ToLEDo Stick V4 470LM 827 E27 SL 0029558

Warranty	3 years
Useful luminous flux (#use)	470

### Technical drawings



### Data table

#### GENERAL DATA

Product name	ToLEDo Stick V4 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	5.0
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959

## ToLEDo Stick V4 470LM 827 E27 SL 0029558

E-number FI	4740964
Warranty	3 years

### OPTICAL DATA

Useful luminous flux (#use)	470
Luminous flux (Rated) (lm)	470
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Power consumption (W)	5
Wattage (W)	5.0
Equivalent watt (W)	40
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	1.8
Inrush Duration ( $\mu$ s)	200
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	220
Max. products per 16A B Breaker	220

### LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000

## ToLEDo Stick V4 470LM 827 E27 SL 0029558

Average life (Rated) (h)	15000
--------------------------	-------

### PHYSICAL DATA

Nominal Product Height (mm)	115
Nominal Product Diameter (mm)	37
Weight (kg)	0.034

### PACKAGING

Product EAN number	5410288295589
Packaging single length / height (cm)	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	12.3
DUN14 (inner)	15410288295586
Units per outer package	6
Packaging outer length / height (cm)	15.4
Packaging outer width (cm)	10.3
Packaging outer depth (cm)	13.7

### SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

# SYLVANIA

ToLEDo Stick V4 470LM 827 E27 SL  
0029558

## Energy label



0029558



5  
kWh/1000h



2019/2015



0029558



5  
kWh/1000h



2019/2015