



## Features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps Same look, size and functionality as incandescent lamps Omni-directional light distribution Suitable replacement for incandescent and halogen lamps Gives same sparkling light effect as incandescent lamp Dimensionally identical to incandescent lamps - fits all fixtures Environment friendly - no mercury and lower CO2 emissions



## Product Overview

Product name	ToLEDo RT G125 V5 CL 1055LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740962
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1
Wattage (W)	8
Power consumption (W)	8
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295459

ToLEDo RT G125 V5 CL 1055LM 827 E27 SL  
0029545

Warranty	3 years
Useful luminous flux (#use)	1055

## Technical drawings



## Data table

### GENERAL DATA

Product name	ToLEDo RT G125 V5 CL 1055LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959

## ToLEDo RT G125 V5 CL 1055LM 827 E27 SL 0029545

E-number FI	4740962
Warranty	3 years

### OPTICAL DATA

Useful luminous flux (#use)	1055
Luminous flux (Rated) (lm)	1055
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Power consumption (W)	8
Wattage (W)	8
Equivalent watt (W)	75
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	Yes
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	4.36
Inrush Duration ( $\mu$ s)	150
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	37
Max. products per 16A B Breaker	18

### LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000

## ToLEDo RT G125 V5 CL 1055LM 827 E27 SL 0029545

Average life (Rated) (h)	15000
--------------------------	-------

### PHYSICAL DATA

Nominal Product Length (mm)	178
Nominal Product Diameter (mm)	125
Weight (kg)	0.135

### PACKAGING

Product EAN number	5410288295459
Packaging single length / height (cm)	19.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0
DUN14 (inner)	15410288295456
Units per outer package	6
Packaging outer length / height (cm)	20.0
Packaging outer width (cm)	80.3
Packaging outer depth (cm)	13.5

### SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

# SYLVANIA

ToLEDo RT G125 V5 CL 1055LM 827 E27 SL  
0029545

## Energy label



0029545



8  
kWh/1000h



2019/2015



0029545



8  
kWh/1000h



2019/2015