



WAGO Lighting Management is a highly sophisticated solution for lighting control in large spaces, such as production facilities and warehouses. Using a combination of predefined hardware and user-friendly software, WAGO offers a lighting management system that facilitates the design and commissioning of new lighting systems while providing numerous additional advantages for their operation. The basic idea: WAGO Lighting Management is ready for the vastly different light requirements of warehouses and production facilities. For example, a production facility can be divided into virtual rooms in which the light can be flexibly adapted. Each virtual room receives signals from sensors and actuators in order to automatically set the appropriate light intensity. Virtual rooms allow quick, easy implementation of both conversions and remodeling via Web configuration.

Notes	
Note	The "Lighting Management" Software is a pre-programmed application based on the CODESYS Development Environment and can be used for both PFC200 G2 Controllers or Touch Panels 600. To download the application and license to the device, WAGOupload software is required, which can be obtained free of charge from the WAGO homepage. Internet connection may be required for license activation.

Software data	
Supported devices	750-8212: PFC200; G2; 2ETH RS Web Panel 400

Delivery	
License type	License for a maximum of 10 DALI lines
Delivery type	License certificate by email (software available for download)
License generation	DRM

Commercial data	
PU (SPU)	1 pcs
Packaging type	not specified
Country of origin	QU
GTIN	4055143962858
Customs tariff number	88888888888

**Product Classification**

ETIM 10.0	EC002537
UNSPSC	43233603
ETIM 9.0	EC002537
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

<b>Compliance Search</b>	
Environmental Product Compliance 2759-204/261-1000	<a href="#">↓</a>

**Documentation**

<b>Manual</b>				<b>Compatibility Information</b>			
Documentation Lighting Management	2.3.0 11.06.2024	pdf 11151.42 KB	<a href="#">↓</a>	Compatibility List DALI Sensors	V 1.2.4 19.02.2025	pdf 516.91 KB	<a href="#">↓</a>

<b>System Description</b>				<b>Tutorial</b>			
Solutions, General Product Information		pdf 321.72 KB	<a href="#">↓</a>	Installation Tutorial Application Controller		mp4 29848.12 KB	<a href="#">↓</a>

<b>Additional Information</b>				<b>Bid Text</b>			
Wiring-Instructions	2.1.0 28.07.2022	pdf 2541.41 KB	<a href="#">↓</a>	Tender text Lighting Management		doc 78.50 KB	<a href="#">↓</a>
Drawing Lighting Management maximum expansion	19.06.2018	pdf 1168.50 KB	<a href="#">↓</a>	2759-204/261-1000		xml 14.20 KB	<a href="#">↓</a>
Drawing Lighting Management minimum expansion	19.06.2018	pdf 464.61 KB	<a href="#">↓</a>	2759-204/261-1000		docx 39.78 KB	<a href="#">↓</a>

<b>Instruction Leaflet</b>			
Beipackzettel Applikationscontroller		pdf 415.00 KB	<a href="#">↓</a>

## Engineering-Software

### Configuration and Commissioning Software

WAGOupload	1.16.1.0 02.02.2022	zip 12111.45 KB	
------------	------------------------	--------------------	---

## Device Files

### Device Driver

KNX Interface Lighting Management	29.01.2018	zip 2.03 KB	
-----------------------------------	------------	----------------	---

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Application

##### 1.1.1.1 Analog input



###### [Item No.: 750-495/000-002](#)

3-Phase Power Measurement; 690 VAC Rogowski coils



###### [Item No.: 750-495](#)

3-Phase Power Measurement; 690 VAC, 1 A



###### [Item No.: 750-495/000-001](#)

3-Phase Power Measurement; 690 VAC, 5 A

##### 1.1.1.2 Bus end module



###### [Item No.: 750-600](#)

End Module

##### 1.1.1.3 DALI interface



###### [Item No.: 753-647](#)

DALI Multi-Master

##### 1.1.1.4 Digital input



###### [Item No.: 750-1405](#)

16-channel digital input; 24 VDC; 3 ms

##### 1.1.1.5 Digital output



###### [Item No.: 750-1504](#)

16-channel digital output; 24 VDC; 0.5 A

### 1.1.1.6 KNX interface



[Item No.: 753-646](#)

KNX/EIB/TP1 Interface

### 1.1.1.7 Power Measurement



[Item No.: 750-495/000-002](#)

3-Phase Power Measurement; 690 VAC Rogowski coils



[Item No.: 750-495](#)

3-Phase Power Measurement; 690 VAC, 1 A



[Item No.: 750-495/000-001](#)

3-Phase Power Measurement; 690 VAC, 5 A

### 1.1.1.8 RTC module



[Item No.: 750-640](#)

Real-time clock Module

### 1.1.1.9 Serial interface



[Item No.: 750-652](#)

RS-232/485 Serial Interface

### 1.1.1.10 Serial Interface RS-232/485



[Item No.: 750-652](#)

RS-232/485 Serial Interface

## 1.1.2 Communication

### 1.1.2.1 EnOcean



[Item No.: 2852-7102](#)

SRE Repeater with ext. ant. / EasySens Radio Repeater



[Item No.: 2852-7101](#)

STC65 RS-485 EVC EnOcean Receiver/ Transmitter with RS-485 EVC interface

### 1.1.2.2 General accessories



[Item No.: 2852-7901](#)

GPS DCF Converter UTC±

### 1.1.3 Current transformer

#### 1.1.3.1 Current transformer terminal block



**Item No.: 2007-8874**

Compact terminal block; for current and voltage transformers; 6,00 mm<sup>2</sup>; multicoloured



**Item No.: 2007-8877**

Compact terminal block; for current transformer circuit; 6,00 mm<sup>2</sup>; multicoloured

### 1.1.4 Power supply

#### 1.1.4.1 Power Supply



**Item No.: 787-1012**

Switched-mode power supply; Compact; 1-phase; 24 VDC output voltage; 2.5 A output current



**Item No.: 787-1007**

Switched-mode power supply; for DALI module (753-647); 1-phase; 18 VDC output voltage; 1.1 A output current; 2,50 mm<sup>2</sup>

### 1.1.5 Radio transmitter

#### 1.1.5.1 EnOcean



**Item No.: 758-940/001-000**

Radio transmitter; EnOcean easyfit PTM 250; 2-channel lighting control



**Item No.: 758-940/003-000**

Radio transmitter; EnOcean easyfit PTM 250; 4-channel lighting control

### 1.1.6 Relay module

#### 1.1.6.1 Relay module



**Item No.: 788-357**

Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; Red status indicator; Module width: 15 mm

### 1.1.7 Sensors

#### 1.1.7.1 Sensor



**Item No.: 2852-7208**

4p4c connection cable, 50 cm



**Item No.: 2852-7215**

Adaptor; Surface mounting set (IP54)



**Item No.: 2852-7207**

DALI HIGHBAY ADAPTER / Control units for light management systems



**Item No.: 2852-7203**

DALI LS/PD LI / Control units for light management systems



**Item No.: 2851-8202**

DALI sensor coupler



**Item No.: 2852-7204**

DALI Sensor Coupler E / DALI sensor coupler for external sensors



**Item No.: 2852-7205**

DALI Sensor Coupler HF LS LI / DALI coupler for radar sensor HF LS LI



**Item No.: 2852-7301**

DALI XC Control Module with 4 freely programmable inputs



**Item No.: 2852-7230**

DALI-Sensor; IR Quattro HD DALI 2



**Item No.: 2852-7231**

DALI-Sensor; IR Quattro SLIM XS DALI 2



**Item No.: 2852-7232**

DALI-Sensor; IS3360 MX Highbay DALI 2



**Item No.: 2852-7233**

DALI-Sensor; IS345 MX Highbay DALI 2

1.1.7.1 Sensor



**Item No.: 2852-7220**

DALI-Sensor; MSensor G3 SRC 30 PIR 5DPI WH



**Item No.: 2852-7221**

DALI-Sensor; MSensor G3 SSM 30 10DPI WH



**Item No.: 2852-7210**

DALI-Sensor; PD11-BMS-FLAT



**Item No.: 2852-7213**

DALI-Sensor; PD4-BMS-GH



**Item No.: 2852-7214**

DALI-Sensor; PD4N-BMS



**Item No.: 2852-7206**

HF LS LI / Control units for light management systems



**Item No.: 2852-7201**

HIGH BAY / Stand-alone motion sensors with switching contact



**Item No.: 2852-7202**

VISION / Stand-alone motion sensors with switching contact



**Item No.: 2851-8201**

WAGO DALI Multi-Sensor Kit