




- Features:**
- Switched-mode power supply
 - Natural convection cooling when horizontally mounted
 - Encapsulated for use in control cabinets
 - Suitable for both parallel and series operation
 - Electrically isolated output voltage (SELV) per UL 61010-1; PELV per EN 60204

Technical data			
Input		Output	
Phases	1	Nominal output voltage $U_{o\,nom}$	24 VDC (SELV)
Nominal input voltage $U_{i\,nom}$	1 x 110 ... 240 VAC	Default Setting	DC 24 V
Input voltage range	1 x 100 ... 264 VAC	Nominal output current $I_{o\,nom}$	5 A (24 VDC)
Nominal mains frequency range	47 ... 63 Hz; 0 Hz	Nominal output power	120 W
Input current I_i	≤ 0.7 A (230 VAC); ≤ 1.6 A (115 VAC)	Deviation	≤ 1 %
Power factor correction (PFC)	Active	Overload behavior	Constant power (in overload range: 1.15 ... 1.4 x $I_{o\,nom}$); Shutdown and automatic restart in the event of a short circuit
Signaling and communication		Efficiency/power losses	
Signaling	1 x LED DC OK (green) 1 x Overload LED (red)	Power loss P_I	≤ 19.5 W (230 VAC; nominal load)
Operation status indicator	Green LED (24 VDC OK) Red LED (overload)	Power loss (max.) $P_{I(max)}$	23.5 W (110 VAC / 24 VDC; 5.5 A)
		Efficiency (typ.)	86 % (230 VAC)
Circuit protection			
Internal fuse	F 3.15 A / 250 VAC		
Backup fusing (recommended)	Circuit breaker: 10 A, 16 A; Tripping characteristic: B or C		



Safety and protection	
Isolation voltage (pri.-sec., AC)	3000 V
Isolation voltage (pri.-PE, AC)	1500 V
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	II
Pollution degree	2
Transient suppression (primary)	Varistor
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes

Connection data	
Connection type 1	Input/output
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 745 Series
Solid conductor	0.08 ... 4 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 4 mm² / 28 ... 12 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Note (conductor cross-section)	12 AWG: THHN, THWN

Physical data	
Width	75 mm / 2.953 inches
Height	92 mm / 3.622 inches
Depth from upper-edge of DIN-rail	136 mm / 5.354 inches

Mechanical data	
Mounting type	DIN-35 rail

Material data	
Fire load	4.8 MJ
Weight	850 g

Environmental requirements	
Ambient temperature (operation)	-10 ... +60 °C
Ambient temperature (storage)	-25 ... +85 °C
Relative humidity	10 ... 96 % (no condensation permissible)
Derating	-4 %/K (> 40 °C; 230 VAC)
Climatic category	3K3 (per EN 60721)



Standards and specifications	
Conformity marking	CE; UKCA
Standards/specifications	EN 61010-1 EN 61204-3 UL 61010-1 SEMI F47 UL 121201 EN IEC 61010-2-201 UL 61010-2-201

Commercial data	
Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 9.0	EC002540
ETIM 8.0	EC002540
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4045454908188
Customs tariff number	85044083900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption
SCIP notification number (Bulgaria)	c5cda720-be2e-42e5-9f2a-5ee3811607c4
SCIP notification number (Czech Republic)	36f49618-4b21-4699-af60-f1fc5941c014

Approvals / Certificates	
General approvals	Declarations of conformity and manufacturer's declarations



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-



Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 787-722	

Documentation			
Bid Text		Instruction Leaflet	
787-722	12.07.2019	xml 6.85 KB	
787-722	12.07.2019	docx 21.09 KB	
		CCC Ex (Additional information)	26.04.2023
		pdf 127.27 KB	
		Primary Switch Mode Power Supply ECO-Power	V 2.2.10 22.07.2024
		pdf 229.55 KB	

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 787-722	EPLAN Data Portal 787-722
	WSCAD Universe 787-722
	ZUKEN Portal 787-722

1 Compatible Products
1.1 Optional Accessories
1.1.1 Tool
1.1.1.1 Operating tool



Item No.: 210-720 Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured	Item No.: 210-769 SCREWDRIVER; green
---	---