Product data sheet Spirotech

Product name

EMCK Maxi 300L max 5,6bar

Product properties

The MultiControl Kompakt MAXI is an automatic expansion and pressure-maintaining device, with 2 pumps (2x 100%) and an overflow valve. An unpressurised expansion tank is integrated.

- contains 2 pumps (2x 100%)
- contains 1 overflow valve (1x 100%)
- Operational pressure range up to 8.1 bar
- Comes with vessel volumes from 45 to 500 liters
- Two further vessels can be added.
- Maximum expansion volume: 75 1,500 litres
- The maximum temperature at the point of connection: 70°C (over 70°C possible with auxiliary tank)
- Maximum safety temperature in the system: 110°C
- Maximum operating pressure (PN): 10 bar


Article number


EMCK-M300-5.6

Product image



Product dimensions







ETIM product data

| Height | 1577 mm |
|--------------------------------|-----------|
| Volume | 300 |
| Max. operating pressure | 5.6 bar |
| Connection | Other |
| Power consumption | 1.1 kW |
| Couplable | Yes |
| Electrical connection | Terminals |
| Function master/slave | No |
| With pressure expansion vessel | Yes |
| Digital control unit | Yes |

| Double pump/compressor unit | Yes |
|--------------------------------------------|-------------|
| With exchangeable membrane | Yes |
| Compressor in base | No |
| Nominal diameter expansion connec- tion | 1 inch (25) |
| Max. medium temperature (continuous) | 70 °C |
| For heating systems up to | 1 MW |
| Horizontal positioning | No |
| Connection voltage | 230 V |
| Article compression class | PN 10 |
| Operating principle | Pump |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



