

## ToLEDo GLS

ToLEDo GLS V6 1521LM 840 E27 SL

0027966



### Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



## PRODUCT OVERVIEW

Product name	ToLEDo GLS V6 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	14
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740567
Warranty	3 years
Luminous flux (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	14
Average life (Nominal) (h)	15000
Product EAN number	5410288279664

## DATA TABLE

### General data

Product name	ToLEDo GLS V6 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	14
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740567

## ToLEDo GLS

ToLEDo GLS V6 1521LM 840 E27 SL

0027966

Warranty	3 years
----------	---------

### Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	14
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	5.25
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	78
Max. products per 16A C Breaker	126
Max. products per 20A C Breaker	158

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	120
Nominal Product Diameter (mm)	60
Weight (kg)	0.056

### Packaging

Single packaging type	Carton
Product EAN number	5410288279664
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (inner)	25410288279668
Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (outer)	15410288279661
Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2

## ToLEDo GLS

*ToLEDo GLS V6 1521LM 840 E27 SL*

0027966

---

<b>Packaging outer depth (cm)</b>	29.7
-----------------------------------	------

### Safety data

<b>Breakage cleaning instructions</b>	Not applicable
<b>Special purpose lamp</b>	No
<b>Dry applications use only</b>	Yes
<b>Suitable for household illumination</b>	Yes
<b>Safety message</b>	Not Suitable for totally enclosed fixtures