

## EK15: Nickel plated eurocone Ø15 (3/4" F)



### Commercial information

Nickel-plated brass screw fitting with 3/4"F connector for 15 mm copper pipe

#### Basic unit dimensions

Height	30 mm
Length	18 mm
Width	30 mm
Net weight	0.047 kg

#### Certificates

ETA, PZH, ITC, TSU, DNV-GL, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	15 Millimetre
Surface protection connection 1	Nickel-plated	Length	18 Millimetre
Material connection 2	Brass	Length of connection 1	10 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	10 Millimetre
Surface protection connection 2	Nickel-plated	Length of connection 2	12.5 Millimetre
Shape	Straight	Working length connection 2	12.5 Millimetre
Reducing	✘	Wrench width	0 Millimetre
Eccentric	✘	Wrench width union nut	0 Millimetre
System specific	✓	Medium temperature (continuous)	-10 70 Degrees celsius
Connection 1	Compression ring	Max. operating pressure at 20 °C	10 Bar
Connection 2	Euroconus (expired)	Standard Dimension Ratio (SDR)	0
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		