



Features

- LED replacement for compact fluorescent Lynx-DE lamps 30,000 hours average rated life (L70 F50) 3 years warranty Quick, simple and safe replacement without rewiring Direct retrofit – easiest way to upgrade existing luminaires to LED technology Suitable for electronic ballast/ ECG ballast and direct mains 220-240V AC operation Compact and durable construction Minimum and maximum operating temperature: -10°C to 40°C Low energy consumption and no flickering Ideal for commercial and residential applications including offices, hotels, restaurants, warehouses, supermarkets, corridors, in addition to living rooms, kitchens and garages Warning: ToLEDo Lynx DE lamps are not suitable for magnetic ballast/ CCG operation

Product Overview

Product name	ToLEDo DE 1000LM G24Q 840 SL
Technology	LED
Watt (Rated) (W)	10
Cap/Base	G24q-3
Fixture rating	Open
E-number FI	4740779
Colour temperature (K)	4000
CRI (Ra)	80
Wattage (W)	10
Product EAN number	5410288280615
Warranty	3 years

Data table

GENERAL DATA

Product name	ToLEDo DE 1000LM G24Q 840 SL
--------------	------------------------------

ToLEDo DE 1000LM G24Q 840 SL 0028061

Technology	LED
Watt (Rated) (W)	10
Cap/Base	G24q-3
Fixture rating	Open
Performance ambient temperature Tq (°C)	25
E-number FI	4740779
Warranty	3 years

OPTICAL DATA

Colour temperature (K)	4000
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	10
Starting time (max) (s)	0.5
Lamp power factor	0.93
Control gear required	No
Inrush Current (A)	20
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	7

LIFETIME DATA

Average life (Rated) (h)	30000
--------------------------	-------

PHYSICAL DATA

Nominal Product Length (mm)	164
Nominal Product Diameter (mm)	35
Weight (kg)	0.09

PACKAGING

ToLEDo DE 1000LM G24Q 840 SL
0028061

Single packaging type	Carton
Product EAN number	5410288280615
Packaging single width (cm)	3.6
Packaging single depth (cm)	3.6
DUN14 (outer)	15410288280612
Packaging outer length / height (cm)	19.2

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Not Suitable for totally enclosed fixtures