

## 38P-2622P: Adapter henco compression x copper press (M,V,SA) 26x22 cusì



### Commercial information

Henco brass press fittings - the best solution for every situation.

38P Brass (CW724) transition pieces straight Henco compression to copper press (V, M and SA profile):

- Suitable for Henco multilayer pipes diameter 26 and 32 mm
- Body material: brass CW724
- Material press sleeves: stainless steel
- Material O-rings: EPDM
- Connection 1: Henco compression 26 or 32 mm
- Connection 2: copper press 22 or 28 mm
- Permitted press profiles: V, M or SA for copper pipe diameter 22 and 28 mm
- Suitable for drinking water and heating
- Press connection equipped with leak detection (Leak Before Press functionality)
- Extremely pressure and temperature resistant
- Equipped with shock ring to prevent electrolysis

#### Basic unit dimensions

Height	56 mm
Length	39 mm
Width	39 mm
Net weight	0.211 kg

#### Certificates

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Utility, Shipbuilding, Industry

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn21Si3P (CW724R)	Outer pipe diameter connection 1	26 Millimetre
Material connection 2	Brass	Wall thickness connecting pipe, connection 1	3 Millimetre
Material quality connection 2	CuZn21Si3P (CW724R)	Outer pipe diameter connection 2	22 Millimetre
Shape	Straight	Wall thickness, connection 2	1.4 Millimetre
Reducing	✓	Length	39.4 Millimetre
Eccentric	✗	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	16 Bar
Nominal diameter connection 1	DN 25	Standard Dimension Ratio (SDR)	0
Connection 1	Compression ring		
Nominal diameter connection 2	DN 20		
Connection 2	Press sleeve		
Main colour fitting	Brass		
Flange compression class (PN)	PN 10		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		