

Interrata Adjustable

INTERRATA ADJUSTABLE L IP67 CLEAR 2000LM 830 MB

0049044




PRODUCT OVERVIEW

Product name	INTERRATA ADJUSTABLE L IP67 CLEAR 2000LM 830 MB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ground recessed
E-number FI	4579507
Warranty	5 years
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	69
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	RG1
Total power consumption (W)	29
Electrical protection	Class I
LED Flickering Rate	Low (6% - 20%)
Housing colour	Stainless steel
IP rating	IP67
IK rating	IK10
Product EAN number	5410288490441

PHOTOMETRY

Interrata Adjustable

INTERRATA ADJUSTABLE L IP67 CLEAR 2000LM 830 MB
0049044



0.5	0.22	E(0°)	3300
	0.23	E(90°)	1650
1.0	0.45	E(0°)	832
	0.46	E(90°)	368
1.5	0.67	E(0°)	368
	0.69	E(90°)	174
2.0	0.89	E(0°)	268
	0.92	E(90°)	97
2.5	1.12	E(0°)	120
	1.15	E(90°)	42
3.0	1.34	E(0°)	97
	1.37	E(90°)	42

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 25.9°)
— C90 - C270 (Half beam angle: 25.2°)

TECHNICAL DRAWINGS

