

## 7-1604-S: Backplate elbow with branch connection 16x1/2"



### Commercial information

The body of the Henco fittings is made from brass CuZn40Pb2 (CW617N).

The fittings are provided with O-rings and a union nut. The compression fittings have a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

Henco screw/compression fittings can be used for all applications with a maximum working pressure up to 10 bar, except for pipes which are built in floors or walls.

The body of the Henco screw/compression fittings is manufactured from brass. The fittings are provided with O-rings and a union nut with a clamping ring. Just like the brass press fittings they are fitted with a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

As in the compression and press fittings range, there are a number of fittings available which allow you to connect copper or steel pipes to Henco pipes.

#### Basic unit dimensions

Height	46 mm
Length	58 mm
Width	45 mm
Net weight	0.131 kg

#### Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Housing material	Brass	Length of connection 1	27 Millimetre
Housing material	Brass	Working length connection 1	27 Millimetre
Material quality	CuZn40Pb2 (CW617N)	Length of connection 2	45 Millimetre
Surface protection	Untreated	Working length connection 2	45 Millimetre
Shape	Right-angled	Working length connection 3	0 Millimetre
System specific	✓	Medium temperature (continuous)	-10 60 Degrees celsius
Nominal diameter connection 2	1/2 inch (15)	Max. operating pressure at 20 °C	10 Bar
Thread size tap connection	1/2 inch		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
Compliant with NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		