



## Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles – 200,000X High lumen efficacy Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast Works only with compatible electronic ballasts Ideal for factories, parking lots, supermarkets, department stores, schools and offices

## Product Overview

<b>Product name</b>	ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840
<b>Technology</b>	LED
<b>Watt (Rated) (W)</b>	37
<b>Lamp shape</b>	Tube, double-ended
<b>Lamp finish</b>	Opal
<b>Fixture rating</b>	Open
<b>General application</b>	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
<b>ETIM Class</b>	EC001959
<b>E-number FI</b>	4940793
<b>Correlated colour temperature (k)</b>	4000
<b>Light colour</b>	Cool White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	6
<b>Beam Angle (°)</b>	150
<b>Photobiological Risk Group</b>	RG0
<b>Wattage (W)</b>	37
<b>Power consumption (W)</b>	37
<b>Dimmable</b>	No
<b>Average life (Nominal) (h)</b>	50000

## ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840 0029271

IP rating	IP20
Product EAN number	5410288292717
Warranty	5 years
Useful luminous flux (#use)	5600

### Technical drawings

