

Product data sheet

Item No. 92.232.5003.3

Cable assembly GST18I3K1B- 15 50GR01

geis® Connection cable female - free end; length: 5m; type GST18I3; 3-pole; 250 V / 16 A; colour of coding: grey with grey strain-relief; cable: H05VV-F 3G1,5, colour: black



Item No.	92.232.5003.3
EAN	4015573680234
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Interlockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	
Color of housing inclusive strain relief	Pebble gray

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 socket
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

Buchsensteil/female connector

Gesamtlänge / total length

Kabel/cable H05VV-F3G1,5
Farbe/colour: siehe Tabelle/see table

Farbe colour	Codierung *X*	Kabelfarbe cable colour
1 schwarz black	N ⊕ L	1 schwarz black
2 weiß white		2 weiß white
3 grau grey	N ⊕ L	3 schwarz black
5 rot red		5 schwarz black

Typ/type: GST18i3K1B- 15 ..

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX03.F	XX in dm-Schritten	92.232.1003.1 = 10dm/L= 1000mm	GST18i3K1B- 15 10SW
U2.232.XX03.F	XX in m-Schritten	U2.232.1203.1 = 12 m/L=12000mm	GST18i3K1B- 15 X12SW
92.232.XX93.F	XX in dm-Schritten	92.232.1093.1 = 10dm/L= 1000mm	

93.F = spezielle Verpackung und Etikettierung nach A 1960.000
special packaging and labelling according to A 1960.000

Freitoleranz nach General tolerance: /

Material: /

Zeichnung Nr./Drawing No.: 92.232.0203.1 01K b

Wieland

PRE-ASSEMBLED CABLE
KONFEKT-LEITUNG
Buchse/female - freies Ende/free end 1.5mm
Crimpschaltung/crimp version K1 250V