


## VB060502-BLAUW: Manifold 1" with ball valves - 2 EK-conections Blue



### Commercial information

Messing Henco verdeler 1" aansluiting met bolkraan en euroconus aansluitingen

- Universele euroconus-aansluitingen
- Per groep afsluitbaar
- Korte inbouwlengthe
- Kan zowel horizontaal als verticaal als ondersteboven geïnstalleerd worden

Beschikbaar in een 3/4" en een 1" uitvoering

Beschikbaar in blauw en rood.

Geschikt voor verwarming, air conditioning en sanitaire installaties.

Via configuratie verdeler mogelijkheid tot parallel gebruik van koude en/of warme circuits.

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 75 mm    |
| Length     | 102 mm   |
| Width      | 40 mm    |
| Net weight | 0.450 kg |

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                    |                                                |                                      |                    |
|------------------------------------|------------------------------------------------|--------------------------------------|--------------------|
| Suitable for tap water             | ✓                                              | Number of branches                   | 2                  |
| Suitable for central heating water | ✓                                              | Number of branching directions       | 1                  |
| Suitable for cooling water         | ✓                                              | Distance between offset              | 50 Millimetre      |
| Suitable for compressed air        | ✗                                              | Max. medium temperature (continuous) | 95 Degrees celsius |
| Suitable for glycol                | ✓                                              | Width                                | 40 Millimetre      |
| Mounting method                    | Surface mounting                               | Height                               | 75 Millimetre      |
| Model                              | Distributor/collector                          | Length distributor                   | 102 Millimetre     |
| Material                           | Brass                                          |                                      |                    |
| Surface protection                 | Galvanised                                     |                                      |                    |
| Shape                              | Throughflow with straight branches             |                                      |                    |
| Nominal diameter connection 2      | 1 inch (25)                                    |                                      |                    |
| Connection 2                       | Internal thread cylindrical BSPP-G (ISO 228-1) |                                      |                    |
| Nominal diameter branches          | 3/4 inch (20)                                  |                                      |                    |
| Connection branches                | Euroconus standardless                         |                                      |                    |
| Deviant distance between branches  | ✗                                              |                                      |                    |
| With filling/drain tap             | ✗                                              |                                      |                    |
| System specific                    | ✓                                              |                                      |                    |
| With shut-off valve                | ✓                                              |                                      |                    |
| With de-aeration                   | ✗                                              |                                      |                    |
| With wall-mounting bracket         | ✗                                              |                                      |                    |
| With mounting material             | ✗                                              |                                      |                    |
| With legs                          | ✗                                              |                                      |                    |
| With insulation                    | ✗                                              |                                      |                    |
| KOMO certified                     | ✗                                              |                                      |                    |
| Type approval according to BBR/EKS | ✗                                              |                                      |                    |