


## Data Sheet | Item Number: 2787-2346

Power supply; Pro 2; 3-phase; 24 VDC output voltage; 10 A output current; Top-Boost + PowerBoost; communication capability

<https://www.wago.com/2787-2346>



### Features:

- Power supply with TopBoost, PowerBoost and configurable overload behavior
- Configurable digital signal input and output, optical status indication, function keys
- Communication interface for configuration and monitoring
- Optional connection to IO-Link, EtherNet/IP™, Modbus TCP or Modbus RTU
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Pluggable connection technology
- Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
- Marker slot for WAGO marking cards (WMB) and WAGO marking strips

### Technical data

Input		Output	
Phases	3	Nominal output voltage $U_{o, nom}$	24 VDC (SELV)
Nominal input voltage $U_{i, nom}$	3 x 400 ... 500 VAC (connection without neutral conductor)	Output voltage range	24 ... 28 VDC (adjustable)
Input voltage range	3 x 340 ... 550 VAC	Default Setting	24 VDC
Nominal mains frequency range	50 ... 60 Hz	Nominal output current $I_{o, nom}$	10 A (24 VDC)
Input current $I_i$	$\leq 3 \times 0.6$ A (400 VAC; 24 VDC / 10 A)	Nominal output power	240 W
Inrush current	$\leq 15$ A (after 1 ms)	Deviation	$\leq 1$ %
Power factor correction (PFC)	Active	Residual ripple	$\leq 70$ mV (peak-to-peak)
Mains failure hold-up time	$\geq 20$ ms (3 x 400 VAC)	Current limitation	$1.1 \times I_{o, nom}$ (typ.)
		Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)
		PowerBoost	15 ADC (5 s)
		TopBoost	Up to 600 %

### Signaling and Communication

Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
-----------	--------------------------------------------------------------------------------------------------------------

### Efficiency/Power Losses

Power loss $P_1$	$\leq 3$ W (standby); $\leq 3$ W (no load); $\leq 18$ W (400 VAC; nominal load)
Efficiency (typ.)	94.1 % (400 VAC; 10 A; 25 °C)

### Circuit Protection

Internal fuse	3 x T 2.5 A / 500 VAC
Pre-fuse (required)	An external DC fuse is required for the DC input voltage.
Backup fuse (recommended)	3 x 16 A (for USA/Canada: 3 x 15 A)

### Safety and protection

Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	0.5 kVDC
Isolation voltage (sec.-signal)	0.5 kVDC
Protection class	I
Protection type	IP20; per EN 60529
Resistance to reverse feed	$\leq 35$ VDC
Overvoltage category	III ( $\leq 2000$ m a.s.l.); II ( $> 2000$ m a.s.l.)
Pollution degree	2
Transient suppression (primary)	Yes
Overvoltage protection; secondary	Internal protective circuit $\leq 35$ VDC (in the event of a fault)
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 1,000,000$ h (per IEC 61709)

### Connection Data

#### Connection 1

Connection type	Input/signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	0.25 ... 1.5 mm <sup>2</sup> / 20 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule	0.25 ... 2.5 mm <sup>2</sup> / 20 ... 14 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

#### Connection 2

Connection type	Output
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 831 Series
Solid conductor	0.5 ... 10 mm <sup>2</sup> / 20 ... 8 AWG
Fine-stranded conductor	0.5 ... 10 mm <sup>2</sup> / 20 ... 8 AWG
Fine-stranded conductor; with insulated ferrule	0.5 ... 6 mm <sup>2</sup>
Fine-stranded conductor; with uninsulated ferrule	0.5 ... 6 mm <sup>2</sup>
Strip length	13 ... 15 mm / 0.51 ... 0.59 inches

### Physical data

Width	50 mm / 1.969 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm

### Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

### Material data

Fire load	0 MJ
Weight	1000 g

### Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Climatic category	3K3 (per EN 60721)
Operating altitude (max.)	5000 m

### Standards and Specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201 SEMI F47 UL 121201 (HazLoc)

### Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4066966137835
Customs tariff number	85044083900

### Product Classification

UNSPSC	39121004
ETIM 9.0	EC002540
ETIM 10.0	EC002540
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03080
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 61010-2-201	UL-US-2209512-0

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Approvals for hazardous areas



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	A-E198726

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2787-2346 [↓](#)

Documentation

Manual			
Product Manual Power supply; Pro 2; 3-phase; 24 VDC output voltage; 10 A output current	V 1.0.1 15.02.2022	pdf 8120.46 KB	<a href="#">↓</a>


Bid Text			
2787-2346	11.05.2022	xml 9.31 KB	<a href="#">↓</a>
2787-2346	11.05.2022	docx 29.81 KB	<a href="#">↓</a>

Instruction Leaflet

Stromversorgung Pro 2	V 1.1.0 03.03.2022	pdf 4602.62 KB	<a href="#">↓</a>
-----------------------	-----------------------	-------------------	-------------------

**CAD/CAE-Data**

**CAD data**  
 2D/3D Models  
 2787-2346 

**CAE data**  
 EPLAN Data Portal  
 2787-2346 

**1 Compatible Products**

**1.1 Product Expansions**

**1.1.1 Communication Module**



**Item No.: 2789-9023**  
 Communication module; EtherNet/IP; MQTT Pub/Sub; communication capability



**Item No.: 2789-9080**  
 Communication module; IO-Link; communication capability



**Item No.: 2789-9015**  
 Communication module; Modbus RTU; RJ45; communication capability



**Item No.: 2789-9052**  
 Communication module; Modbus TCP; communication capability

**1.2 Optional Accessories**

**1.2.1 Cables and connectors**

**1.2.1.1 Communication cable**



**Item No.: 750-923/000-001**  
 Configuration cable; USB connector; Length: 5 m

**1.2.3 Marking**

**1.2.3.1 Marker**



**Item No.: 2009-115**  
 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

**1.2.3.2 Marker carrier**



**Item No.: 2789-1233**  
 Marker carrier; for WMB or marking strips; Length: 33 mm

**1.2.3.3 Marking strip**



**Item No.: 2009-110**  
 Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

## 1.2.4 Tool

### 1.2.4.1 Operating tool



**Item No.: 210-720**

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



**Item No.: 210-721**

Operating tool; Blade: 5.5 x 0.8 mm; with a partially insulated shaft; multicoloured