

VBS060503-RO: Manifold 1" with valves and eurocone connection 1"x3xEK14,16,18 & 20 R



Commercial information

- O-ring connection + alignment
- Universal euroconus connections
- Lockable by circuit
- Short installation length
- Can be installed both vertical, horizontal or upside down
- Available in a 3/4" and a 1" version
- Available in red and blue. Optionally green levers are available.
- Suitable for the realization of heating, air conditioning and sanitary installations
- Manifolds configuration permit the realization of hot and/or cold circuits in parallel.

Basic unit dimensions

Height	75 mm
Length	146 mm
Width	47 mm
Net weight	0.585 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	3
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	45 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	47 Millimetre
Mounting method	Surface mounting	Height	75 Millimetre
Model	Distributor/collector	Length distributor	146 Millimetre
Material	Brass		
Surface protection	Untreated		
Shape	Other		
Nominal diameter connection 2	1 inch (25)		
Connection 2	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)		
Nominal diameter branches	3/4 inch (20)		
Connection branches	Euroconus (expired)		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✗		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		