



### Features

- LED exterior surface mounted luminaire, 350mm diameter, 1450lm as max. lumen output, 15W max. power consumption, 97lm/W efficacy, 3000K color temperature, CRI80, IP66, IK10, 60,000 hours (L70), white housing, vandal resistant. DALI and DALI 2 dimming compatibility. Integrated emergency, 3 hours, supplied with anti-theft screws

### Product Overview


<b>Product name</b>	START SURFACE IP66 1450LM 830 IK10 DALI EM3 WHT
<b>Technology</b>	LED
<b>Cap/Base</b>	N/A
<b>Housing</b>	PC Polycarbonate
<b>Mount</b>	Ceiling surface mounting
<b>Environment</b>	Indoor, Outdoor
<b>Fixture luminous flux (lm)</b>	1450
<b>Luminaire efficacy (lm/W)</b>	86
<b>LOR (%)</b>	100
<b>Colour temperature (K)</b>	3000
<b>Light colour</b>	Warm White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	6
<b>Glare control</b>	< 25
<b>Photobiological Risk Group</b>	RG0
<b>Total power consumption (W)</b>	17
<b>Electrical protection</b>	Class II
<b>Control gear type</b>	LED driver constant current
<b>Control gear mounting</b>	Integrated
<b>LED Flickering Rate</b>	Ultra low (5% or less)
<b>Housing colour</b>	RAL9003

Light your world

## START SURFACE IP66 1450LM 830 IK10 DALI EM3 WHT 0049249

IP rating	IP66
IK rating	IK10
Product EAN number	5410288492490
Warranty	5 years
Colour Code	830

### Photometry



### Technical drawings

