INSAVER 220 SURFACE MOUNTED

INSAVER UGR19 220 2500LM 840 SM

0030517

Product features

- Insaver is a surface mounted LED downlight ,Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 20W; 2500lm; 125lm/W; 4000K; UGR <19 with height of 95 mm. Meets TP(a) requirements.

PRODUCT OVERVIEW

Product name	INSAVER UGR19 220 2500LM 840 SM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4278546
Warranty	5 years
Useful luminous flux (Fuse)	2500
Fixture luminous flux (lm)	2500
Luminaire efficacy (lm/W)	125
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	70
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK07
Product EAN number	5410288305172

PHOTOMETRY

© Feilo Sylvania | Date Printed: 31 Mar 2025

INSAVER 220 SURFACE MOUNTED

INSAVER UGR19 220 2500LM 840 SM

0030517





TECHNICAL DRAWINGS



© Feilo Sylvania | Date Printed: 31 Mar 2025