

## 17HNA-12-X: HN75 bracket connection R2,5" male inox



### Commercial information

The Super Size range includes the Henco multilayer pipe and Henco fittings with diameters of 75-90, with reducers to diameters of 32-40-50-63. The connectors ensure a complete multilayer pipe system with numerous variations for headers and risers. The many combination possibilities and the revolutionary connection technology make this modular system extremely flexible.

Like all Henco press fittings, the Super Size fittings come with leak detection and are made from high-performance plastic PVDF. These properties make the Henco Super Size fittings suited for different applications, such as drinking water installations, heating installations and installations in the chemical and food industries.

#### Basic unit dimensions

Height	62 mm
Length	80 mm
Width	80 mm
Net weight	0.670 kg

#### Certificates

KIWA

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Laboratory, Utility

## Technical characteristics

Material connection 1	Stainless steel	Bend radius	0 Millimetre
Material quality connection 1	Stainless steel 316 L (1.4404)	Outer pipe diameter connection 1	75 Millimetre
Surface protection connection 1	Untreated	Length	80 Millimetre
Surface treatment connection 1	Untreated	Tightening torque	0 0 Newtonmetre
Material connection 2	Stainless steel	Medium temperature (continuous)	-10 70 Degrees celsius
Material quality connection 2	Stainless steel 316 L (1.4404)	Max. operating pressure at 20 °C	10 Bar
Surface protection connection 2	Untreated	Standard Dimension Ratio (SDR)	0
Surface treatment connection 2	Untreated		
Shape	Straight		
Reducing	✘		
Eccentric	✘		
System specific	✓		
Connection 1	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)		
Nominal diameter connection 2	2 1/2 inch (65)		
With buffer stud	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✘		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		