

## 47P-25H26: Transition Coupling U-TH-H 25x2,5mm to Henco 26x3,0



### Commercial information

#### Basic unit dimensions

Height	33 mm
Length	72 mm
Width	33 mm
Net weight	0.116 kg

#### Certificates

KIWA

#### Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend angle	0 Degrees
Surface protection connection 1	Untreated	Bend radius	0 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 1	25 Millimetre
Material connection 2	Brass	Outer pipe diameter connection 2	26 Millimetre
Surface protection connection 2	Untreated	Wall thickness connecting pipe, connection 2	3 Millimetre
Surface treatment connection 2	Untreated	Length	72 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Model	1-part	Max. operating pressure at 20 °C	16 Bar
Reducing	✓	Max. operating pressure at max. medium temperature	16 Bar
Eccentric	✗		
System specific	✗		
Connection 1	Press sleeve		
Connection 2	Press sleeve		
Contour code connection 2	TH		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With thermal insulation	✗		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✓		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
Certified according to NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Gastec QA - AR 214 (H2)	✗		
Type approval according to BBR/EKS	✗		