

M-BMINI3: Kit: recharg.pressmach+batt.18v+charger+case+mother jaw+ 16-20-26



Commercial information

This pressing tool is available in 3 versions: the M-BMINI3 (with mother jaws and inserts TH16-20-26), the M-BMINI3-F (with full jaws TH16-20-26) and the M-BMINI3-S (without jaws or inserts). Characteristics of the pressing tool: Light, compact and robust:

- This pressing tool is available in 3 versions: the M-BMINI3 (with mother jaws and inserts TH16-20-26), the M-BMINI3-F (with full jaws TH16-20-26) and the M-BMINI3-S (without jaws or inserts). Characteristics of the pressing tool:
- Light, compact and robust
- Electronic monitoring
- Rotation 360° ensures efficient operation even in limited working space
- Housing made of insulating, shock-resistant polyamide, fibre-glass reinforced
- Ergonomic two-component handle for effortless one-handed operation
- Compatible with the press jaws of Novopress and Rothenberger, as well as with Klauke MAP2L19
- Manual return possible
- 2-year warranty or 20,000 cycles from the 25th cycle onwards, stored in the machine's memory
- LED indicators provide quick information about the status of the machine and the presses
- High quality metal case for safe storage
- Monitor the performance of the device via USB interface and free software

Basic unit dimensions

Height	410 mm
Length	480 mm
Width	110 mm
Net weight	9.693 kg

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Underfloor Heating, Gas, Sanitary

Solutions

Building installations, Industry, Underfloor heating, Oil & gas, Utility, Shipbuilding

Technical characteristics

Operation	Battery (rechargeable)	Suitable for pipe diameter	14 26 Millimetre
Suitable for steel tube	✗	Nominal voltage	18 Volt
Forced process	✓	Battery capacity	2 Ampere hour
Automatic switch-off	✓	Number of included batteries	1
With case	✓	Length	480 Millimetre
With charging cradle	✓	Weight	9.7 Kilogram