



17HNA-08-X: HN75 bracket connection R6/4" male inox



Commercial information

The Super Size range includes the Henco multilayer pipe and Henco fittings with diameters of 75-90, with reducers to diameters of 32-40-50-63. The connectors ensure a complete multilayer pipe system with numerous variations for headers and risers. The many combination possibilities and the revolutionary connection technology make this modular system extremely flexible.

Like all Henco press fittings, the Super Size fittings come with leak detection and are made from high-performance plastic PVDF. These properties make the Henco Super Size fittings suited for different applications, such as drinking water installations, heating installations and installations in the chemical and food industries.

Basic unit dimensions

| | |
|------------|----------|
| Height | 78 mm |
| Length | 45 mm |
| Width | 78 mm |
| Net weight | 0.450 kg |

Certificates

KIWA

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Laboratory, Utility

Technical characteristics

| | | | |
|------------------------------------|---|----------------------------------|------------------------|
| Material connection 1 | Stainless steel | Bend radius | 0 Millimetre |
| Material quality connection 1 | Stainless steel 316 L (1.4404) | Outer pipe diameter connection 1 | 75 Millimetre |
| Surface protection connection 1 | Untreated | Length | 45 Millimetre |
| Surface treatment connection 1 | Untreated | Tightening torque | 0 0 Newtonmetre |
| Material connection 2 | Stainless steel | Medium temperature (continuous) | -10 70 Degrees celsius |
| Material quality connection 2 | Stainless steel 316 L (1.4404) | Max. operating pressure at 20 °C | 10 Bar |
| Surface protection connection 2 | Untreated | Standard Dimension Ratio (SDR) | 0 |
| Surface treatment connection 2 | Untreated | | |
| Shape | Straight | | |
| Reducing | ✘ | | |
| Eccentric | ✘ | | |
| System specific | ✓ | | |
| Connection 1 | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) | | |
| Nominal diameter connection 2 | 1 1/2 inch (40) | | |
| With buffer stud | ✘ | | |
| High tensile strength | ✘ | | |
| With thermal insulation | ✘ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✘ | | |
| Capped | ✘ | | |
| With connection indicator | ✘ | | |
| With drain valve | ✘ | | |
| With de-aerator | ✘ | | |
| FM quality mark | ✘ | | |
| LPCB quality mark | ✘ | | |
| ULC quality mark | ✘ | | |
| UL quality mark | ✘ | | |
| DIN-CERTCO certificate | ✘ | | |
| VdS quality mark | ✘ | | |
| With approval for TÜV | ✘ | | |
| DVGW quality mark for gas | ✘ | | |
| DVGW quality mark for water | ✘ | | |
| KIWA certified | ✓ | | |
| Gastec QA mark | ✘ | | |
| KOMO certified | ✘ | | |
| Type approval according to BBR/EKS | ✘ | | |